

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other ☐
2. NAME OF OPERATOR
Bedford, Inc.
3. ADDRESS OF OPERATOR
P.O. Box 255, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1450' fnl 1450' fel
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Drilling to Total Depth

5. LEASE
SF-03110-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
None
7. UNIT AGREEMENT NAME
None
8. FARM OR LEASE NAME
Ram
9. WELL NO.
1-A
10. FIELD OR WILDCAT NAME
WAW-Fruitland - PC.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
S8-T26N-R12W, N.M.P.M.
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
30-045-23339
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5966 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

July 26, 1979 - Drilled 4 3/4" hole to total depth of 1314 ft. Ran electrical, gamma-ray and density log to T.D. Ran 41 jts 2 7/8", 6.5#, J-55, 10Rnd., NUE casing to 1310 ft. with two centralizers. Cemented with 100 sacks 50/50 Class B-Pozmix cement with 1/4#/sack D-29 cellophane flakes, 2% gel, 2% CaCl., followed with 50 sacks Class B neat slurry with 2% CaCl. Held 1500# pressure on casing while waiting 24 hrs. for cement to set. Will attempt completion later.

Subsurface Safety Valve: Manu. and Type _____

Set @ AUG 21 1979 Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. M. SPEER

TITLE

Agent

DATE

July 28, 1979

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

W. M. SPEER