

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY**

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other

2. NAME OF OPERATOR  
Dome Petroleum Corp.

3. ADDRESS OF OPERATOR  
501 Airport Dr., Suite 107, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL & 990' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

5. LEASE  
Noo-C-14-20-2038

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Navajo

7. UNIT AGREEMENT NAME.

8. FARM OR LEASE NAME  
Dome Old Trading Post

9. WELL NO.  
2

10. FIELD OR WILDCAT NAME  
Bisti-Lower Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 15, T26N, R14W

12. COUNTY OR PARISH: 13. STATE  
San Juan NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6249 GR.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Spud & set surface			

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 12½" hole at 7:00 PM 1-27-79. Drilled to 225'. Ran 5 joints (205') 8 5/8", 23#, K55, ST&C Casing. Casing landed at 219' KB. Cemented with 200 sacks Class "B" cement with 3% CaCl. Plug down at 2:45 AM 1-28-79. Circulated cement.


Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Hollingsworth TITLE Drilling Foreman DATE 12-2-79

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL IF ANY:



\*See Instructions on Reverse Side

NMOCC