

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR
Mobil Oil Corporation

3. ADDRESS OF OPERATOR
9 Greenway Pl. Ste. 2700, Hou., TX 77046

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FEL & 660 FNL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: same as surface

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

(other) rpt of DST & ☒ Plugging operations ☐

SUBSEQUENT REPORTS OF

RECEIVED

JUN 12 1984 (NOTE:

OIL CON. DIV.
DIST. 3

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/2/79 - Ran GR & BBC Acoustic 6881-1600

6/2/79 - Ran GR & BBC Acoustic 6881-1600
6/3/79 - Cond mud for DST #1 6760-6881, SI in 2-1/2 hrs, initial FP 40-53, initial SIWHI
133, 2nd BHFP 53-67, 2nd BHSIF 214, rec. 451' drlg. mud w/no show.

6/4/79 - 133, 2nd BHFP 53-67, 2nd BHSIP 214, rec. 451 drif. mud w/no show.
DST #2 6380-6460 by Howco, TP/35, SI in 1½ hrs open on 1/4" ck., gas cut mud to
surf in 10 min. rec brackish wtr. w/tr. oil, SI 2 hrs, POH rec DP full of
brackish wtr. 0.116 Ohms resistivity, continue to test through 6/7/79.

6/8/79 - Howco spot 66 sxs Lt. Wt. @ 6500-6300 & 65 sxs. 5600-5400.

6/8/79 - Howco spot 66 sxs Lt. wt. @ 3500 3500
6/9/79 - Verbal permission to P & A Granted by USGS/Farmington.
6/10/79 - 1000 3600 30 3200-2000 1

6/9/79 - Verbal permission to P & A Granted by USGS/Farmington.
6/9/79 - Howco set 130 sx Lt. Wt. 4000-3600, 80 sx 2200-2000, 110 sx B 1700-1500, 30
sx 0-50. rel rig 12:30 AM, Well P & A.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robbie Jay TITLE Authorized Agent DATE 7/11/79

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL IF ANY:

RECEIVED

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

• See Instructions on Reverse Side

ACCEPTED FOR RECORD

JUN 11 1969 JUL 16 1979

TERMINATION: 225 JUNE 1964
U. S. GEOLOGICAL SURVEY
Y ~~PIA~~ *[Signature]* LANSING, MICH.