

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

## 2. NAME OF OPERATOR

Jerome P. McHugh

## 3. ADDRESS OF OPERATOR

Box 208, Farmington, NM 87401

## 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1450' FNL - 1850' FEL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

## 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

## SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

## 5. LEASE

NM 12028

## 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## 7. UNIT AGREEMENT NAME

## 8. FARM OR LEASE NAME

Chaco Plant

## 9. WELL NO.

3A

## 10. FIELD OR WILDCAT NAME

WAW Fruitland PC

## 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 20 T26N R12W

## 12. COUNTY OR PARISH

San Juan

## 13. STATE

NM

## 14. API NO.

## 15. ELEVATIONS (SHOW DF, KDB, AND WD)

6018' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.1)

## 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 1240'. Moved in and rigged up Wellex Logging Co. Ran IES log to TD. Rigged up csg tools. Ran 42 jts 2-7/8" OD 6.4# CW-55 10R NEUE tbq for csg. TE 1241.35' set @ 1240' GR. Had good mud returns and reciprocated pipe while cementing. Preflushed hole w/100 gals CW-7. Cemented w/40 sx 65-35 w/12% gel w/1/4# flo cele per sx followed by 50 sx class "B" neat w/4% gel w/1/4# flo cele per sx. Bumped plug w/1500 psi - released to 800 psi. Shut in. POB 3:05 p.m. 8-17-79.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_ Ft.

## 18. I hereby certify that the foregoing is true and correct

SIGNED

Thomas A. Dugay

TITLE Petroleum Eng.

DATE

8-21-79

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: