

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-431-C for such proposals.

1. oil ☐ gas ☒ well ☒ other ☐
2. NAME OF OPERATOR
Jerome P. McHugh
3. ADDRESS OF OPERATOR
Box 208, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)
1450' FNL - 1850' FEL
AT SURFACE
AT TOP PROD. INTERVAL
AT TOTAL DEPTH

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT OFF ☐	☐
FRACTURE TREAT ☐	☐
SHOOT OR ACIDIZE ☐	☐
REPAIR WELL ☐	☐
PULL OR ALTER CASING ☐	☐
MULTIPLE COMPLETION ☐	☐
CHANGE ZONES ☐	☐
ABANDON* ☐	☐
(other) ☐	☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)
10-29-79

Moved in and rigged up FWS swabbing unit. Ran 34 jts 1-1/4" IOR 2.4# EUE tbq set @ 1106.5' GR. TE 1107.97'. Hit sand bridge @ 1120'. No show of gas. Shut well in, rigged down FWS.

5. LEASE
NM 12028
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Chaco Plant
9. WELL NO.
(3A) 35
10. FIELD OR WILDCAT NAME
WAW Fruitland PC
11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA
Sec 20 T26N R12W
12. COUNTY OR PARISH 13. STATE
San Juan NM
14. APPLIED
15. ELEVATIONS (SHOW DE, KDB, AND WDB)
6018' GR

(NOTE: Report results of multiple completion or zone change on Form 9-431-C)

Subsurface Safety Valve: Make and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

Thomas A. Dugan
Thomas A. Dugan

TITLE Agent

DATE

10-30-79

Set @ _____ Ft.

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL IF ANY

TITLE

DATE

*See Instructions on Reverse Side

NMOCC

*See Instructions on Reverse Side