

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR

DOME PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR 501 Airport Drive,
Suite 107, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1760' FNL, 1840' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐

(other) RUN PRODUCTION CASING

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to 1386'. Ran 45 jts., 2 7/8", 6.5#, J-55 EUE casing. Casing landed at 1375' GL. Cemented with 100 sacks 65/35 Pozmix with 6% gel and 1/4# Floseal/sack. Followed with 50 sacks class "B" cement with 2% CaCl and 1/4# Floseal/sack. Plug down at 1:15 PM, 07/02/79.



Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Hollingsworth TITLE DRILLING FOREMAN DATE July 3, 1979
H. D. HOLLINGSWORTH

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL _____

TITLE _____

DATE _____

* See Instructions on Reverse Side

NMDC

