Form 9-331 Dec. 1973

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

	Form Approved.  Budget Bureau No. 42–R1424		
	/5. LEASE		
	/ N.M. 0560223		
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
-			
	7. UNIT AGREEMENT NAME		
nt			
	8. FARM OR LEASE NAME		
	Frew Federal		
	9. WELL NO.		
	16		
	10. FIELD OR WILDCAT NAME		
	WAW Fruitland-Pictured Cliff		
	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
7	AREA		
	Sec. 19, T26N, R12W		
	12. COUNTY OR PARISH 13. STATE		
	San Juan New Mexico		

(Do not use this form for proposals to drill or to deepen or plug back to a lift reservoir. Use Form 9-331-C for such proposals.) 1. oil gas XFEB 9 well other well OIL CON. COM. 2. NAME OF OPERATOR DOME PETROLEUM CORP. 3. ADDRESS OF OPERATOR 3600 Southside River Rd., Farmington, 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1 AT SURFACE: 1490' FSL, 1800' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

SUBSEQUENT REPORT OF:

RECEIVED
(NOTE
) FEB 0 5 1992

14. API NO.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

15. ELEVATIONS (SHOW DF, KDB, AND WD) 6116 GR

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON\*
(other) Well Workover

REQUEST FOR APPROVAL TO:

U. S. CEOLOGICAL SURVEY FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in completion unit and rigged up. Swabbed Pictured Cliff Perforations 1200'-1206' for 2 hours. Recovered water with trace of gas. Rigged up perforators and set cast iron bridge plug at 1195'. Pressure tested plug to 1500 psi for 30 min. Held OK. Swabbed well to 800'. Perforated Pictured Cliff Formation from 1180'-1183' with 2 1/8" gun. 4 shots/ft. Swabbed well dry. Flowed well 4 hrs. Well making 231 MCF/Day. No water. Shut well in for Potential Test.

Subsurface Safety Valve: Manu. and Type	Set @ Ft.		
18. I hereby certify that the foregoing is true and correct			
SIGNED H. D. HOLLINGSWOrth TITLE Area Prod. Supt. DATE	February 5, 1982		
(This space for Federal or State office use)			
APPROVED BY TITLE D CONDITIONS OF APPROVAL, IF ANY:	ATE		

ABULPILD FOR RECORD

\*See Instructions on Reverse Side

FEB 8 1981

NMOCC

FARMINGTON DISTHICT