UNITED STATES

5. LEASE	
0560222	

DEPARTMENT OF THE INTERIOR	NM 0560223
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
1. oil c gas 🛪	PREW FEDERAL
well well other 2. NAME OF OPERATOR	9. WELL NO.
DOME PETROLEUM CORP.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 501 Airport Drive. Suite 107, Farmington, NM 87401	WAW FRUITLAND-PICTURED CLIFF 11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990' PEL. 790' PSL.	AREA SEC. 29, T26N, R12W 12. COUNTY OR PARISH 13. STATE
AT SURFACE: 990' FEL, 790' FSL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	SAN JUAN NEW MEXICO
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6020 GR
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) SPUD AND SET SURFACE CASING 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner Spudded 8 3/4" hole at 10:30 AM, 06/22/79. Dr: 20#, K-55 ST&C casing. Casing landed at 42' GI class "B" cement with 2% CaCl. Plug down at 1: cement.	irectionally drilled, give subsurface locations and to this work.)* illed to 46'. Ran 1 jt. 7", Cemented with 35 sacks
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED	OLOGICAL SURVE NINGTON, N. M. Set @
(This space for Federal or State of	ice use)
APPROVED BY TITLE TITLE	DATE