

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-3148-7

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator ODESSA NATURAL CORPORATION ATTN: John Strojek	8. Farm or Lease Name Burroughs-State
3. Address of Operator P.O. Box 3908 Odessa, Texas 79760	9. Well No. 1-E
4. Location of Well UNIT LETTER K 1450' FEET FROM THE South LINE AND 1820 FEET FROM West THE LINE, SECTION 36 TOWNSHIP 26N RANGE 11W NMPM.	10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 6391' K.B.	12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/11/79 Spud Well
9/11/79 T.D. 264'. Ran 8 joints 8-5/8", 24.0 lb. K-55 casing (241.52') set at 256.60' with 250 sacks Class "B" Cement with 3% Calcium Chloride and 1/4 lb. Flocele per sack. Cement circulated. Pressure test with 500 psig. Test ok.
9/22/79 T.D. 6329'. Ran 147 joints 4-1/2", 10.50 & 11.60, K-55 casing (6323.76') set at 6327.95' with:
First Stage: 480 sacks 50-50 Pozmix with 6-1/4 lbs. Gilsonite and 6 lbs. salt per sack.
Second Stage: 410 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs. Gilsonite per sack, followed by 50 sacks Class "B" Neat Cement. Stage Collar 1853'
Third Stage: 310 sacks 65-35 Pozmix (12% Gel) with 6-1/4 lbs. Gilsonite per sack, followed by 50 sacks Class "B" Neat Cement. Stage Collar 4436'.

FOR: ODESSA NATURAL CORPORATION

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY
EWELL N. WALSH

President, Walsh Engineering
& Production Corporation

SIGNED Ewell N. Walsh, P.E.

TITLE

DATE 9/27/79

Original Signed by A. R. Kendrick

TITLE

SUPERVISOR DISTRICT # 3

DATE

SEP 28 1979

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY: