5. LEASE

UNITED STATES

DEPARTMENT OF THE INTERIOR	N00-14-20-8376 🌲 💆 🧭 🗸
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Usk Ye Ni Tah Blackie 🖫
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME 2 2 2 2
(Do not use this form for proposals to drill or to deepen or plug back to a different	77 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
reservoir, Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME 👸 👙 🗒
1. oil a gas vvv	Dietrich Exploration 28G:
1. oil ☐ gas ⋊⊠x other	9. WELL NO. ခွဲ့ ချွန္ခြဲ မ မ မွာမွဲမွာ
2. NAME OF OPERATOR	<u> </u>
Dietrich Exploration Company, Inc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 602 Midland Savings Bldg.	WAW - P. C. FruitTand
444 17th STreet, Denver, Colorado 80202	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA 5.135 5
below.) AT SURFACE: 1850' FNL and 1850' FEL	
AT TOP PROD. INTERVAL: Same	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH: Same	San Juan New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. AFT NO. 12.4 12.6 3
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	6064 G.L. 3 3 3 3 3 8
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	े प्रकृत प्रमुख्य
TEST WATER SHUT-OFF	
FRACTURE TREAT SHOOT OR ACIDIZE	then the state of
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING []	change on Form 9-330.)
MULTIPLE COMPLETE	Section of the sectio
CHANGE ZONES U	· · · · · · · · · · · · · · · · · · ·
ABANDON* (other) Change of plans	
(olio)	<u> </u>
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates,	
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* (*** *******************************	
1) Surface pipe to be 91' of 7" 23# used casi	ing. Cemented with 50 sacks
Class "B" + 2% CaCl ₂ .	성용충보통 시 중 중요 불리
.	
2) Ojo Alamo top is estimated to be 90'. The	
cemented to surface by using a cement volume of caliper + 20% excess.	
Filler cement will be 65-35 pox mix with 1	2% gel and P.C. Fruitland will
be covered with class "B" cement. Verific	cation of coverage will be made
by temperature survey.	or submitted for the control of the
	Heldue held between the Heldue held held held held held held held hel
•	원칙적으로 무현 생각으로
	Sent Sent Sent Sent Sent Sent Sent Sent
Subsurface Safety Valve: Manu. and Type	Set @Ft.
18. I hereby certify that the foregoing is true and correct	100 mg / mg
O Ola la A Annt	6 16 70 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
SIGNED TITLE AGENT	DATE 37-70-79-

*See Instructions on Reverse Side

(This space for Federal or State office use)

___ TITLE ___

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY: