

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
Southern Union Exploration Company

3. ADDRESS OF OPERATOR
1217 Main St., Dallas, TX 75202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1840' FNL & 1010' FWL
AT TOP PROD. INTERVAL: Perforations @ 526-530'
AT TOTAL DEPTH: PBD @ 974'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input checked="" type="checkbox"/>

(other) ☐

5. LEASE
N.M. 33029

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
SX - Federal

9. WELL NO.
#2-21

10. FIELD OR WILDCAT NAME
Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 21, T26N, R13W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6360' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-25-80 Well drilled to 1595'TD. 2 7/8" tubing was run & cemented to surface. Perforated from 1526-32' & tested the PC formation. Set tubing plug @ 974'. Perforated from 526-530' & tested the Fruitland. Well pumped 12 bbls of cement into formation @ 526-530' and cemented to surface. Cut off 4' below ground level & cleaned up location.

Subsurface Safety Valve: Manu. and Type None **ACCEPTED FOR RECORD** Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James F. Sims TITLE Drilling & Production Supt. DATE APR 22 1981
January 6, 1981

APPROVED BY James F. Sims TITLE BY RE DATE

CONDITIONS OF APPROVAL IF ANY: JUN 25 1982

APPROVED

JAMES F. SIMS
DISTRICT ENGINEER

NMOCC

*See Instructions on Reverse Side

