UNITED STATES

IJ.	LEASE	•	
	N.M.	33029	

DEPARTMENT OF THE INTERIOR	N.M. 33029
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME SX - Federal
1. oil gas X other	9. WELL NO.
2. NAME OF OPERATOR Southern Union Exploration Company 3. ADDRESS OF OPERATOR	#1-21 10. FIELD OR WILDCAT NAME Pictured Cliffs
1217 Main St., Dallas, TX 75202	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA 2/ Sec3+, T26N, R13W
AT SURFACE: 800' FSL & 1840' FEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE San duan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)	(NOTE: Report results of multiple completion or zone such a such
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine	directionally drilled, give subsurface locations and
11-18-79, Reached TD of 1465'. Ran 2 7/8" tub Perforated @ 1405-09' & 1433-36'. Set tubing at 950'. Attempt to squeeze cement to surface Wiper plug hung after 1 bbl flush away. Well of 2 7/8" tubing. Will cut off 4' below groun	plug @ 1000', perforated . Cement was circulated, cemented inside and out
Subsurface Safety Valve: Manu. and TypeNone	Set @ Ft
18. I hereby certify that the foregoing is true and correct Drilling &	pt. DATE January 6, 1981
APPROVED space for Federal or State of	ffice use)

CONDITIONS OF APPROVAUNT MY 1982 JAMES F. SIMS
DISTRICT ENGINEER

*See Instructions on Reverse Side