

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Robert L. Bayless

3. ADDRESS OF OPERATOR

P.O. Box 1541, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 800' FSL & 1840' FEL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Re-enter ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

NM 33029

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Moncisco Mesa

9. WELL NO.

#1

10. FIELD OR WILDCAT NAME

Farmington

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 21, T26N, R13W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6200' G.L.

RECEIVED

JUL 5 1983

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-30-83 Move in and rig up Bayless Rig 6. Pressure test 2-7/8" casing to 3000 psi. Held OK. Tripped bit and 1 1/4" tubing in the hole. Tagged hard spot at 126' RKB. Drilled on hard spot for approximately 30 minutes and fell through. Tagged cement at 197' RKB. Drilled 113' of cement to 310' RKB. SDFN.

7-1-83 Tripped tubing out of hole. Pressure tested casing to 3000 psi. Held OK. Tripped tubing and bit in the hole. Drilled 276' of cement to 586'. SDFN.

7-2-82 SD for Holiday.

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Operator

DATE

JULY 5, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OIL CON. DIV.

DIST. 3

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

JUL 07 1983

NMOCC

FARMINGTON, N. M.
CY