	E. ant Bureau Ny. 42-R14; 4
	/
	1000-0-14-20-740.
CBCLCCC L 3 /	E. IF INDIAN, ALLOTTEE OR TRIBE NAME  NAVAJO
CONTRACTOR AND SERVICE OF WILLIAM	7. UNIT AGREEMENT NAME
in one une this form for proposals to critical to greenen or peur back to a different section 1997 (1998). 1440 for such proposals	0. [10]
	8. FARM OR LEASE NAME
r r CC <u>e otner</u> r r <del>C</del> weil <b>E</b> otner	DOME NAVAJO 18-26-12
L. WEME OF OPERATOR	9. WELL NO.
DI II PERROLDINI CORPORATION	10 5151 0 00 400 000 5 14445
A REPRESE OF CHERATOR TO SEE A FINCET Drive	18. FIELD OR WILDOAT NAME   WAM FRUITLAND-FICTURED CLIFF
Suite 107, Farmington, New Memico 87401	
L LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
below.)	1
AT SURPACE: 790' FSL, 790' FWL	Sec. 18, T26N, R12N  12. COUNTY OR PARISH: 13. STATE
AT TOP PROD. INTERVAL:	12. COONTY ON PARISH 13. STATE
AT TOTAL DEPTH;	14. API NO.
. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6049 'GR
EPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9-330.)
HANGE ZONES  BANDON*  Ther) REVISIONS TO APD	
HANGE ZONES  SANDON*  Ther) REVISIONS TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	irectionally drilled, give subsurface locations and it to this work.)*  St BOP before drilling out from und
HANGE ZONES  SANDON*  ther) REVISIONS TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen  1. Install 6" 900 series Double Ram BOP. Tes surface pipe. Test pipe rams daily. Test	irectionally drilled, give subsurface locations and it to this work.)*  St BOP before drilling out from und blind rams on trips.
#ANGE ZONES  #ANDON*  ther) REVISIONS TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen  1. Install 6" 900 series Double Ram BOP. Test surface pipe. Test pipe rams daily. Test  2. Drill 7 7/8" hole to 90'. Run 90' of 5½",	irectionally drilled, give subsurface locations and it to this work.)*  St BOP before drilling out from uncertainty the blind rams on trips.  15.5#, K-55 surface casing. Ceme
HANGE ZONES  BANDON*  ther) REVISIONS TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen  1. Install 6" 900 series Double Ram BOP. Test surface pipe. Test pipe rams daily. Test  2. Drill 7 7/8" hole to 90'. Run 90' of 5½", with 75 sacks class "B" cement with 2% CaC	irectionally drilled, give subsurface locations and it to this work.)*  St BOP before drilling out from und blind rams on trips.  15.5#, K-55 surface casing. Cement.  Cl. Circulate tement.
HANGE ZONES  BANDON*  ther) REVISIONS TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen  1. Install 6" 900 series Double Ram BOP. Test surface pipe. Test pipe rams daily. Test  2. Drill 7 7/8" hole to 90'. Run 90' of 5½", with 75 sacks class "B" cement with 2% CaC	irectionally drilled, give subsurface locations and it to this work.)*  St BOP before drilling out from und blind rams on trips.  15.5#, K-55 surface casing. Ceme
HANGE ZONES  SANDON*  ther) REVISIONS TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen  1. Install 6" 900 series Double Ram BOP. Test surface pipe. Test pipe rams daily. Test  2. Drill 7 7/8" hole to 90'. Run 90' of 5½", with 75 sacks class "B" cement with 2% CaC  ABOUT TO SACKS CLASS "B" cement with 2% CaC  ABOU	irectionally drilled, give subsurface locations and at to this work.)*  St BOP before drilling out from und blind rams on trips.  15.5#, K-55 surface casing. Cement.  CI. Circulate gement.  Set
HANGE ZONES  BANDON*  ther) REVISIONS TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen  1. Install 6" 900 series Double Ram BOP. Test surface pipe. Test pipe rams daily. Test  2. Drill 7 7/8" hole to 90'. Run 90' of 5½", with 75 sacks class "B" cement with 2% CaC  ABELIANS  ABELIANS  ADDITIONAL CLEAR OF THE STANDON OF THE STAND	irectionally drilled, give subsurface locations and at to this work.)*  St BOP before drilling out from uncertainty to blind rams on trips.  15.5#, K-55 surface casing. Cement.  CI. Circulate tement.  St. Set OREMANI October 2, 1979

