

Dist: 0+4 (BLM); 1-File; 1-Acctng, 1-Crystal; 1-Bayless

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Merrion Oil & Gas Corporation

3. Address and Telephone No.

610 Reilly Avenue, Farmington, NM 87401-2634 (505) 327-9801

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1850' fnl & 790' fel (SENE)
Section 10, T26N, R13W, NMPM

H

5. Lease Designation and Serial No.

NM-12235

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Southland 6

9. API Well No.

30-045-23803

10. Field and Pool, or Exploratory Area

WAW Fruitland P.C.

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Re-perf & Acidize

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/19/96 MIRU JC Well Service. Killed well with 16 bbls of water. ND wellhead, no tubing in well. RU Petro Wireline and run GR-CCL, found fill at 1295'. Re-perforate from 1294'-1281' with 2 spf (13' - total of 26 holes). RD Petro WL. Install 2-7/8" master valve.

11/20/96 WO stimulation.

11/21/96 RU Halliburton nitrogen and acid trucks. Pump 500 gals of 15% HCl with 70Q foam at 5 bpm, flushed with 3500 scf of nitrogen. Max. pressure 500#, treat at 482#, ISIP 250#. RD Halliburton. Open well and left flow to atmosphere thru 1/2" choke.

11/22/96 MIRU JC Well Service. Found well venting gas. RD flowlines and master valve. Install tubing head. Tally & TIH with 39 jts of 1-1/4", 2.4#, EUE tbg (1255.10') and landed at 1260' KB. (Perfs 1281'-1294' and fill at 1295'). NU WH. RDMOL.

14. I hereby certify that the foregoing is true and correct

Signed Steven S. Dunn Ind. Pr. & Prod Manager

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____

ACCEPTED FOR RECORD

12/1/96

DEC 16 1996

FARMINGTON DISTRICT OFFICE