n=1711	Form Androved.
	+0+14+20+7411
	E. IF INDIAN, ALLOTTES OF TEISE NAME
to the state of th	CONTAGREEMENT WAS
a nut use this form for proposals to drill on to beeden or plug back to a different. From 5 Solish for such proposals.	8. FARM OR LEASE NAME
	DOME NAVAJO 13-26-1
A. [9. WELL NO.
LANCE OF OPERATOR	10. FIELD OR WILDOAT NAME
a vidoja <u>kariozaja (j. 1949.)</u> 1. konstanta en entretanta (j. 1949.) pro esta t iri ta	A THE SECTION AND SECTION OF CAREER
Edite 107, Tarmington, Mile Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY C
below.	STC. 13, %26N, F13W
AT SURFACE: 1520 FALL, FOLUT FALL AT TOP PRODUNTERVAL	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	SAN JUAN NEW MENICO 14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WI
EOUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6013 GE
THE OB ALTED CACING '	(NOTE: Report results of multiple completion or zo
PULL OR ALTER CASING	change on Form 9–330.)
TRITIFIE COMPLETE THE TRITIFIE COMPLETE THE TRITIFIE	
CHITTELE COMPLETE SHANGE ZONES SHANDON* State() REVISIONS TO ARE.	change on Form 9-330.) Ite all pertinent details, and give pertinent date directionally drilled, give subsurface locations are
HANGE ZONES BANDON* COMET: PEVISIONS TO APE. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating any proposed work. If well is	change on Form 9-330.) Ite all pertinent details, and give pertinent date directionally drilled, give subsurface locations are to this work.)* Est before drilling out from under the change of the control of the change of the
HANGE ZONES BANDON* Cther' PEVISIONS TO APE. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statinciple including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 1. Install 6" 900 series Double Ram BOP. Te	change on Form 9-330.) Inte all pertinent details, and give pertinent date directionally drilled, give subsurface locations are not to this work.)* Inst before drilling out from under the blind rams on trips. The control of the
### CHANGE ZONES #### CHANGE ZONES ###################################	change on Form 9-330.) Interaction and pertinent details, and give pertinent date directionally drilled, give subsurface locations are not to this work.)* Inst before drilling out from under the blind rams on trips. In 15.5#, K-55 surface casing. In 2% CaCl. Circulate cement.
### CHANGE ZONES #### CHANGE ZONES ###################################	change on Form 9-330.) Inte all pertinent details, and give pertinent date directionally drilled, give subsurface locations are not to this work.)* Inst before drilling out from under the blind rams on trips. In 15.5#, K-55 surface casing. In 2% CaCl. Circulate cement.
CHANGE ZONES BANDON* Cther) PRYISIONS TO APE. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 1. Install 6" 900 series Double Ram BOP. Te surface pipe. Test pipe rams daily. Tes 2. Erill 7 7/8" hole to 90'. Run 90' of 5½" Cement with 75 sacks class "B" cement with	change on Form 9-330.) Interaction and pertinent details, and give pertinent date directionally drilled, give subsurface locations are not to this work.)* Instruction of the subsurface details on the subsurface of the subsurface casing. In 15.5#, K-55 surface casing. In 2% CaCl. Circulate cement.
### CHANGE ZONES BANDON** Cther** PEYISIONS TO APE. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 1. Install 6" 900 series Double Ram BOP. Te surface pipe. Test pipe rams daily. Tes 2. Erill 7 7/8" hole to 90'. Run 90' of 5½" Cement with 75 sacks class "B" cement with	change on Form 9-330.) Interaction and pertinent details, and give pertinent date directionally drilled, give subsurface locations are not to this work.)* Instructionally drilled, give subsurface locations are not to this work.)* Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.)
HANGE ZONES BANDON* Timer's PEVISIONS TO APE. 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 1. Install 6" 900 series Double Ram BOP. Te surface pipe. Test pipe rams daily. Tes 2. Erill 7 7/8" hole to 90'. Run 90' of 5½" Cement with 75 sacks class "B" cement with	change on Form 9-330.) Inte all pertinent details, and give pertinent date directionally drilled, give subsurface locations are not to this work.)* Inst before drilling out from under the blind rams on trips. In 15.5#, K-55 surface casing. In 2% CaCl. Circulate cement.
HANGE ZONES BANDON* Cther) PEVISIONS TO APE. 7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 1. Install 6" 900 series Double Ram BOP. Te surface pipe. Test pipe rams daily. Tes 2. Erill 7 7/8" hole to 90'. Run 90' of 5½" Cement with 75 sacks class "B" cement with REC OCT U. S. CO FAR	change on Form 9-330.) Interaction and pertinent details, and give pertinent date directionally drilled, give subsurface locations are not to this work.)* Instructionally drilled, give subsurface locations are not to this work.)* Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.)
### PANGE ZONES BANDON** CTURET PEYISIONS TO APE. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine 1. Install 6" 900 series Double Ram BOP. Te surface pipe. Test pipe rams daily. Test 2. Erill 7 7/8" hole to 90'. Run 90' of 5½" Cement with 75 sacks class "B" cement with REC OCT Subsurface Safety Valve: Manu. and Type 18. Thereby certify that the foregoing is true and correct	change on Form 9-330.) Interaction and pertinent details, and give pertinent date directionally drilled, give subsurface locations are not to this work.)* Instructionally drilled, give subsurface locations are not to this work.)* Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.) Instructionally drilled, give subsurface locations are not to this work.)

Cleaf