THE COLOR OF THE PROPERTY OF T	1   1 10 1   Mean No. 47-R1404
A FIRST COLOR OF THE PROPERTY OF SUBSEQUENT REPORT OF:  THE CONTROL OF SUBSECUENT REPORT OF SUBSEQUENT REPORT OF:  THE CONTROL OF SUBSECUENT REPORT OF:  THE CONTROL O	
RECEIVED  RECEIV	parata
8. FARMORE  5. FARMORE  6. FARMORE  7. WELL NO.  6. FARMORE  7. WELL NO.  6. FARMORE  6. FARMORE  6. FARMORE  6. FARMORE  6. FARMORE  7. WELL NO.  6. FARMORE  6.	ALLOTTUE OR TRIBE NAME
DATE MANAGE  1. NUL OF DEFICE  1. SEC. T. R.  AREA  Sec. 13. T.  12. COUNTY O.  SAN JUAN  14. API NO.  15. ELEVATION  16. CHECK APPROPRIATE DOX TO INDICATE NATURE OF NOTICE.  REPORT, OR OTHER DATA  15. ELEVATION  16. CHECK APPROPRIATE DOX TO INDICATE NATURE OF NOTICE.  REPORT, OR OTHER DATA  16. CHECK APPROPRIATE DOX TO INDICATE NATURE OF NOTICE.  REPORT, OR OTHER DATA  17. EST WATER SHUTLOFF  RECULES FOR APPROVAL TO:  SUBSEQUENT REPORT OF:  18. ELEVATION  19. WELL NO.  11. SEC. T. R.  AREA  Sec. 13. T.  12. COUNTY O.  SAN JUAN  14. API NO.  15. ELEVATION  6068'. GR.  16. CHECK APPROPRIATE DOX TO INDICATE NATURE OF NOTICE.  REPORT OF NOTICE.  REPORT OF NOTICE.  REPORT OF NOTICE.  16. CHECK APPROPRIATE DOX TO INDICATE NATURE OF NOTICE.  REPORT OF NOTICE.  REPORT OF NOTICE.  16. CHECK APPROPRIATE DOX TO INDICATE NATURE OF NOTICE.  REPORT OF NOTICE.  17. SEC. T. R.  AREA  Sec. 13. T.  12. COUNTY O.  SAN JUAN  14. API NO.  6068'. GR.  (NOTE. Report of change  15. ELEVATION  6068'. GR.  (NOTE. Report of change  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent de including estimated date of starting any proposed work. If well is directionally drilled including estimated date of starting any proposed work. If well is directionally drilled including estimated date of starting any proposed work. If well is directionally drilled including estimated date of starting any proposed work. If well is directionally drilled including estimated date of starting any proposed work. If well is directionally drilled including estimated date of starting any proposed work. If well is directionally drilled including estimated date of starting any proposed work. If well is directionally drilled including estimated date of starting any proposed work. If well is directionally drilled including estimated date of starting any proposed work	IENSTAT WANTE
DATE MANAGE  9. WELL NO.  10. FIELD CR V.  11. SEC., T., R.  AREA  LOCATION OF WELL REPORT LOCATION CLEARLY. See space 17  become 17. TOP FROIL INTER- AL  AT TOP FROIL INTER- AL  AT TOTAL DEPTH:  18. CHECK APPROPRIATE COX TO INDICATE NATURE OF NOTICE.  REPORT, OR OTHER DATA  EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  EST WATER SHUT-OFF  REACTURE TREAT  HOOT OR ACIDIZE  EPAIR WELL  DIL OR ALTER CISING  THALE COMPLETE  PRINCIPLES  THALE COMPLETE  PRINCIPLES  TO APP  10. FIELD CR V.  AREA  Sec. 13. T.  12. COUNTY O.  SAN JUAN.  14. APPINC.  15. ELEVATION  6068'. GR  (NOTE Report of change  That COMPLETE  BANDON'S  THE BROWN OF THE CONTROL OF STAN APPINCATIONS (Clearly state all pertinent de including estimated cate of starting any proposed work. If well is directionally drilled measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams  2. Drill 7 7/8" surface hole to 90'. Run 90' of 55", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVEL  OCT 0 4 1979  U. S. GEOLOGICAL SUI  U.	FASE NAME
9. WELL NO.  ADDRESS OF SPECIAL  AT TOTAL DEPTH:  C. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.  REPORT, OR OTHER DATA  EQUEST FOR APPROVAL TO:  SUBSEQUENT REPORT OF:  EST WATER SHUT-OFF RACTURE TREAT  HOOT OR ACIDIZE  EPAIR WELL  MILL OR ALTER CASING  TILLE COMPLETE  ADDRESS OF SPECIAL STREET  ANAGE ZONES  BANDONS  BANDONS  TO ESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent de including estimated date of starting any proposed work. If well is directionally driller measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams  2. Drill 7 7/8" surface hole to 90'. Run 90' of 5½", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVED  OCT 0 4 1979  U. S. GEOLOGICAL SUI U. S. GEOLOGICAL SU	<u>C 13-26-13</u>
10. FELDER VILLE STATE OF THE PROPERTY OF THE	<u></u>
SOUTH 107, Parrington, New Mexico 87401  L. LOCATION OF WELL REPORT LOCATION CLEARLY. See space 17 below AT TOP PRODUCTED AND AND AND AND AND AND AND AND AND AN	ALDON NIVE
A LCOATION OF WELL REPORT LOCATION CLEARLY. See space 17 beco.  FI CIRFACE: 1121' FSL, 790' FWL AT TOP PROC BITCH-42. AT TOTAL DEPTH:  C. CHECK APPROPRIATE DOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  EST WATER SHUT-OFF RACTURE TREAT HOTO OR ACIDIZE EPAIR WELL  DIL OR ALTER COSING HANGE ZONES BANDONS  BANDONS  THAT COMPLETE  AREA  Sec. 13, T. 12. COUNTY O. 14. API NC.  15. ELEVATION 6068' GR  (NOTE: Report of change)  (NOTE: Report of change)  THAT COMPLETED  HANGE ZONES BANDONS  BANDONS  THAT COMPLETED  (NOTE: Report of change)  THAT COMPLETED OPERATIONS (Clearly state all pertinent de including estimated date of starting any proposed work. If well is directionally drilled measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams 2. Drill 7 7/8" surface hole to 90'. Run 90' of 55,", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVED  OCT 0 4 1979  U. S. GEOLOGICAL SUI	AALLER OTUTOD CLIFT II, M., CR BLK, AND SURVEY O
AT TOP PROC. INTEALABLE AT TOP PROC. INTEALABLE AT TOTAL DEPTH:  C. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  EST WATER SHUT-OFF RACTURE TREAT HOOT OR ACIDIZE EPAIR WELL ULL OR ALTER CASING TABLE COMPLETE HANGE ZONES BANDON*  PREVISIONS TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent de including estimated date of starting any proposed work. If well is directionally driller measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams  2. Drill 7 7/8" surface hole to 90'. Run 90' of 5½", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVEL  OCT 0 4 1979  U. S. GEOLOGICAL SUI	,, , , , , , , , , , , , , , ,
AT TOTAL DEPTH:  AT TOTAL DEPTH:  C. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  EQUEST FOR APPROVAL TO:  SUBSEQUENT REPORT OF:  EST WATER SHUT-OFF RACTURE TREAT  HOOT OR ACIDIZE  EPAIR WELL  ULL OR ALTER CASING  LITHE COMPLET  ANDON*  OTHER DEPTH OF APP  (NOTE Report of change)  TO DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent de including estimated date of starting any proposed work. If well is directionally drilled measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams  2. Drill 7 7/8" surface hole to 90'. Run 90' of 5½", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVEL  OCT 0 4 1979  U. S. GEOLOGICAL SUI U. S. GEOLOG	
AT TOTAL DEPTH:  C. CHECK APPROPRIATE DOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  EST WATER SHUT-OFF RACTURE TREAT HOOT OR ACIDIZE EPAIR WELL  ULL OR ALTER CASING EMADONS  MINET REPORT TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent de including estimated date of starting any proposed work. If well is directionally drilled measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams  2. Drill 7 7/8" surface hole to 90'. Run 90' of 5½", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVED  OCT 0 4 1979  U. S. GEOLOGICAL SUI U. S. GE	DR PARISH 13. STATE
14. APPROPRIATE EQX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  SIT WATER SHUT-OFF RACTURE TREAT HOOT OR ACIDIZE EPAIR WELL  ILL OR ALTER CASING  ILL HANGE ZONES BANDON*  PENISTENS TO APP  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent de including estimated date of starting any proposed work. If well is directionally drilled measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams  2. Drill 7 7/8" surface hole to 90'. Run 90' of 5½", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVED  OCT 0 4 1979  U. S. GEOLOGICAL SUI U. S. GEOLOGICAL	MEW MEXICO
15. ELEVATION  EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  EST WATER SHUT-OFF RACTURE TREAT HOOT OR ACIDIZE EPAIR WELL ULL OR ALTER CASING LITTLE COMPLETE HANGE ZONES BANDON*  DITTLE COMPLETE HANGE ZONES BANDON*  THE COMPLETE OPERATIONS (Clearly state all pertinent de including estimated date of starting any proposed work. If well is directionally driller measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams  2. Drill 7 7/8" surface hole to 90'. Run 90' of 5½", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVED  OCT 0 4 1979  U. S. GEOLOGICAL SUI U.	
EQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  SET WATER SHUT-OFF RACTURE TREAT HOOT OR ACIDIZE EPAIR WELL ULL OR ALTER CASING THANGE ZONES BENNDON* WHAT REVISIONS TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent de including estimated date of starting any proposed work. If well is directionally drilled measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams 2. Drill 7 7/8" surface hole to 90'. Run 90' of 5½", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVED  OCT 0 4 1979  U. S. GEOLOGICAL SUI U. S.	MC (CLICW DE IVER AND W
SUBSEQUENT REPORT OF:  STATE WATER SHUT-OFF HOOT OR ACIDIZE  EPAIR WELL  ULL OR ALTER CASING  TITLE COMPLETE  HANGE ZONES  BANDONS  MINER  PEVISIONS TO APD  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent de including estimated date of starting any proposed work. If well is directionally drilled measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams  2. Drill 7 7/8" surface hole to 90'. Run 90' of 5½", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVED  OCT 0 4 1979  U. S. GEOLOGICAL SUI	NS (SHOW DF, KDB, AND WI
including estimated date of starting any proposed work. If well is directionally drilled measured and true vertical depths for all markers and zones pertinent to this work.)*  1. Install 6" 900 series Double Ram BOP. Test before dr surface pipe. Test pipe rams daily. Test blind rams  2. Drill 7 7/8" surface hole to 90'. Run 90' of 5½", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVED  OCT 04 1979  U. S. GEOLOGICAL SUI U. S. GEOLOGICAL SUI FARMINGTON, N. M. Subsurface Safety Valve: Manu. and Type  18. Thereby certify that the foregoing is true and correct	results of multiple completion or zo on Form 9–330.)
surface pipe. Test pipe rams daily. Test blind rams  2. Drill 7 7/8" surface hole to 90'. Run 90' of 5½", 15 casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVED  OCT 04 1979  U. S. GEOLOGICAL SUR FARMINGTON, N. M. FARMINGTON, N. M. FARMINGTON, N. M.	etails, and give pertinent date d, give subsurface locations a
casing. Cement with 75 sacks class "B" cement with 2 cement.  RECEIVED  OCT 0 4 1979  U. S. GEOLOGICAL SUI  FARMINGTON, N. M.  FARMINGTON, N. M.  SIGNED SOLUTION FOREMAN DATE  TITLD PRICE & PROD FOREMAN DATE	
RECEIVEL  OCT 04 1979  U. S. GEOLOGICAL SUI  U. S. GEOLOGICAL SUI  FARMINGTON, N. N.  FARMINGTON, N. N.  TITLDRLG & PROD FOREMAN DATE	
Subsurface Safety Valve: Manu. and Type  18. I hereby certify that the foregoing is true and correct  TITLDRLG & PROD FOREMAN DATE	
18. I hereby certify that the foregoing is true and correct  TITLE PRIG & PROD FOREMAN DATE	
TITLE RLG & PROD FOREMAN DATE	Set @
TITLDRLG & PROD FOREMAN DATE	- • •
H. D. HOLZ NGSWORTH	October 2, 1979
(This space for Federal or State office use)	<del></del>

