

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ Dry Hole

2. NAME OF OPERATOR  
Kerr-McGee Corporation

3. ADDRESS OF OPERATOR  
P. O. Box 250, Amarillo, Texas 79189

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 660' FWL  
AT TOP PROD. INTERVAL: 1980' FNL & 660' FWL  
AT TOTAL DEPTH: 1980' FNL & 660' FWL

15. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED  
MAR 17 1992  
OIL CON. D  
DIST. 3

5. LEASE  
N00-C-14-20-2937

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Navajo

7. UNIT AGREEMENT NAME  
N/A

8. FARM OR LEASE NAME  
Navajo

9. WELL NO.  
2-5

10. FIELD OR WILDCAT NAME  
Wildcat

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA  
Sec. 5, T-26, R-14W

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.  
N/A

15. ELEVATIONS (SHOW DE KDB, AND WD)  
5918' DF; 5920' KDB; 5905' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On February 29, 1980, TD was reached.  
On March 1, 1980, this well was plugged as follows:  
Plug #1 4765-4615 w/50 sx C1 "B" Cement  
Plug #2 3580-3430 w/50 sx C1 "B" Cement  
Plug #3 1070- 570 w/160 sx C1 "B" Cement  
Plug #4 368- 235 w/50 sx C1 "B" Cement  
Plug #5 10-0 w/10 sx C1 "B" Cement

A 4" Dry hole marker was cemented into 9 5/8" casing 4' above ground level.  
March 2, 1980, ED MORT

Subsurface Safety Valve: Manu. and Type N/A Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kelly Eisenberg; Engineering Assistant; March 17, 1980

(This space for Federal or State office use)

APPROVED BY TITLE DATE

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

ctions on Reverse Side

APPROVED  
AS AMENDED

FARMINGTON COPY

DEC 19 1981

J. H. MILLER  
AREA MANAGER