3-21-80:

UNITED STATES DEPARTMENT OF THE INTERIO **GEOLOGICAL SURVEY**

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill on to deepen or plug back to a different exercicly, his form 9-331-6 for such perspectation. (Do not use this form for proposals to drill on to deepen or plug back to a different exercicly, his form 9-331-6 for such perspectation. (Do not use this form for proposals to drill on to deepen or plug back to a different exercicly, his form 9-331-6 for such perspectation. (Do not use this form for proposals to drill on to deepen or plug back to a different exercicly, his form 9-331-6 for such perspectation. (Do not use this form for proposals to drill on to deepen or plug back to a different exercicle. In column 1 to the form 9-331-1 to 1 t	Form 9-331 Dec. 19/3	Form Approved. Budget Bureau No. 42-R1424
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposable to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposable, or such propo	UNITED STATES	/
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-Clor such proposals.) 1. oil	DEPARTMENT OF THE INTERIOR	•
Huerfano Unit	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1. oil well	(Do not use this form for proposals to drill or to deepen or plug back to a different	Huerfano Unit
2. NAME OF OPERATOR E1 Paso Natural Gas Company 3. ADDRESS OF OPERATOR Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below.) 800 'S, 1800 'W AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE FROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent datals, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 18. PBTD 6685'. Tested casing to 4000#, OK. Perfed 6432,6434,6436,6438,6457,6461,6465,6502,6509,6512,6515,6518,6521,6583,6586' W/1 SPZ. Fraced w/73,750# 20/40 sand, § 40,000# 10/20 sand, 55,000 gal. wtr. Flushed w/ 100 gal. wtr. Subsurface Safety Valve: Manu, and Type	1 nil ggs	
3. ADDRESS OF OPERATOR Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 800'S, 1800'W AT SURFACE: AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOPA ROPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF BY SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE DULL OR ALTER CASING MULTIPLE COMPLETE DOES ABANDON* (cother) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work if well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. PESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work if well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. PETD 6685'. Tested casing to 4000#, OK. Perfed 6432, 6434, 6436, 6438, 6457, 6461, 6465, 6502, 6509, 6512, 6515, 6518, 6521, 6583, 6586' W/1 SP2. Fraced w/73, 750# 20/40 sand, § 40,000# 10/20 sand, 55,000 gal. wtr. Flushed warr. Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type Ft.	well well well well other	` -
Basin Dakota Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 800 'S, 1800 'W AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 12. COUNTY OR PARRISH 13. STATE San Juan 14. API NO. 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6475 'GL 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, measured and true vertical depths for all markers and zones pertinent to this work.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, measured and true vertical depths for all markers and zones pertinent to this work.) 18. PPBTD 6685'. Tested casing to 4000#, OK. Perfed 6432,6434,6436,6438,6457,6461,6465,6502,6509,6512,6515,6518,6521,5583,6586' W/1 SPZ. Fraced w/73,750# 20/40 sand, § 40,000# 10/20 sand, 55,000 gal. wtr. Flushed w 2400 gal.wtr. Subsurface Safety Valve: Manu. and Type Set @ Ft.		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 800 'S, 1800 'W AT SURFACE: AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 17. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF REPACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL REPAIR WELL REPAIR WELL REPAIR WELL REPAIR WELL REPORT COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. PBTD 6685'. Tested casing to 4000#, OK. Perfed 6432,6434,6436,6438,6457,6461,6465,6502,6509,6512,6515,6518,6521,6583,6586' W/1 SPZ. Fraced w/73,750# 20/40 sand, § 40,000# 10/20 sand, 55,000 gal. wtr. Flushed w. 2400 gal. wtr. Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Type Ft. 18. I hereby gertify that the foregoing is true and correct		
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 17. REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 18. SIANT ON REPAIR SAND WE SAND WE SAND WE SAND WE SAND WE SHOW THE SAND WE SAND WE SHOW THE SAND WE SHOW THE SAND WE SHOW THE SAND WE SHOW THE SAND WE SHAW THE SAND WE SHOW THE SAND WE SHOW THE SAND WE SHOW THE SAND WE SHOW THE SAND WE SHAW THE SAND WE SHAW THE SAND WE SHOW THE SAND WE SHAW THE SAND WE SHOW THE SAND WE SHAW THE SAND WE SHAW THE SAND WE SHOW THE SAND WE SHAW THE SAND WE	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 800'S, 1800'W	AREA Sec. 7, T-26-N, R-10-W
14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 16. CHECK APPROPOSED TO: 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. PBTD 6685'. Tested casing to 4000#, OK. Perfed 6432,6434,6436,6438,6457, 6461,6465,6502,6509,6512,6515,6518,6521,6583,6586' W/1 SPZ. Fraced w/73,750# 20/40 sand, § 40,000# 10/20 sand, 55,000 gal. wtr. Flushed w 2400 gal.wtr. Subsurface Safety Valve: Manu. and Type	=	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REPORT, OR OTHER DATA REPORT, OR OTHER DATA REPORT, OR OTHER DATA SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6475 ' GL 6475 ' GL (NOTE: Report results of multiple completion or zone change on Form 9-330.) (NOTE: Report results of multiple completion or zone change on Form 9-330.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 18. PBTD 6685 '. Tested casing to 4000#, OK. Perfed 6432,6434,6436,6438,6457, 6461,6465,6502,6509,6512,6515,6518,6521,6583,6586 ' W/1 SPZ. Fraced w/73,750# 20/40 sand, & 40,000# 10/20 sand, 55,000 gal. wtr. Flushed w 2440 gal.wtr. Subsurface Safety Valve: Manu. and Type	AT TOTAL DEPTH:	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL WILTIPLE COMPLETE CHANGE ZONES BABANDON* (Including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* PBTD 6685'. Tested casing to 4000#, OK. Perfed 6432,6434,6436,6438,6457,6461,6465,6502,6509,6512,6515,6518,6521,6583,6586' W/1 SPZ. Fraced w/73,750# 20/40 sand, § 40,000# 10/20 sand, 55,000 gal. wtr. Flushed w 2400 gal.wtr. Subsurface Safety Valve: Manu. and Type Set @ Ft. 18. I hereby certify that the foregoing is true and correct	16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 12. PBTD 6685'. Tested casing to 4000#, OK. Perfed 6432,6434,6436,6438,6457,6461,6465,6502,6509,6512,6515,6518,6521,6583,6586' W/1 SPZ. Fraced w/73,750# 20/40 sand, § 40,000# 10/20 sand, 55,000 ga1. wtr. Flushed w/ 2400 ga1.wtr. Subsurface Safety Valve: Manu. and Type Set @ Ft. 18. I hereby certify that the foregoing is true and correct	REQUEST FOR APPROVAL TO: SUBSECUENT REPORT OF	
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* PBTD 6685'. Tested casing to 4000#, OK. Perfed 6432,6434,6436,6438,6457,6461,6465,6502,6509,6512,6515,6518,6521,6583,6586' W/1 SPZ. Fraced w/73,750#20/40 sand, & 40,000# 10/20 sand, 55,000 gal. wtr. Flushed w/2400 gal.wtr. Subsurface Safety Valve: Manu. and Type	TEST WATER SHUT-OFF	
6461,6465,6502,6509,6512,6515,6518,6521,6583,6586' W/1 SPZ. Fraced w/73,750# 20/40 sand, § 40,000# 10/20 sand, 55,000 gal. wtr. Flushed w/ 2400 gal.wtr. Subsurface Safety Valve: Manu. and Type Set @ Ft.	Including estimated date of starting any proposed work. It wall is di	rectionally drilled give subsurface locations and
18. I hereby certify that the foregoing is true and correct	6461,6465,6502,6509,6512,6515,6518,6521,6583	,6586' W/1 SPZ. Fraced w/73,750#
	Subsurface Safety Valve: Manu. and Type	Set @ Ft.
SIGNED No. 11 July Drilling Clerk Date March 24, 1980	18. I hereby certify that the foregoing is true and correct	
	SIGNED A. J. J. S. TITLE Drilling Cle	rk DATE March 24, 1980

SERVICES /

Ex Tropical والاوام المسورية

Subsurface Safety Valve: Manu. and Type	e	Set @ Ft.
18. I hereby certify that the foregoing is	true and correct	
SIGNED D. Dusco	TITLE <u>Drilling Clerk</u> DA	тв <u>March</u> 24, 1980
	(This space for Federal or State office use)	
APPROVED BY	TITLE C	ATE
		AGREPTED FOR RECORD

*See Instructions on Reverse Side