UNITED STATES

| P.O. Box 507, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 790 FNIL & 1790 FWL AT SURFACE: 790 FWL AT SURFACE: | UNITED STATES | 5. LEASE |
|--|---|--|
| SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form to proposals to drift or to deepon or plug back to a different reservor. Use from 2-312-06 true proposals) 1. oil gas other Sunday Other 2. NAME OF OPERATOR Other Other 3. ADDRESS OF OPERATOR Other 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 5. SECTION 34. T281. RIZEN 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT OTHER SHUT-OFF FRACTURE TREAT OTHER SHUT-OFF OTHER DATA OTHER CALLED OTHER DATA OTHER DATA OTHER CALLED OTHER DATA OTHER CALLED OTHER DATA OTHER CALLED OTHER DATA OTHER CALLED OTHER DATA OTHER DATA OTHER CALLED OTHER DATA OTH | DEPARTMENT OF THE INTERIOR | NOO-C-14-20-7470 |
| SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use from 5-31-C or suce proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use from 5-31-C or suce proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use from 5-31-C or suce proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use from 5-31-C or suce proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use from 5-31-C or suce proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use from 5-31-C or suce proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use from 5-31-C or suce proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use from 5-3-3-C or suce proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use the suce proposal to the form 5-3-3-C or suce proposals.) (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use the form 5-3-C or suce proposal to deepen or plug back to a different reservoir. Use the form 5-3-C or suce proposal to the full of the suce proposal to the full of the suce proposal to the full of the suce proposal to a different reservoir. Use the full of the full of the full of the full of the full or f | ***AMENDED*** GFOLOGICAL SURVEY | |
| SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form top proposals to ediff or to deepon or plus back to a different reteroof, besign proposals to ediff or to deepon or plus back to a different reteroof, besign proposals to ediff or to deepon or plus back to a different reteroof, besign proposals to ediff or to deepon or plus back to a different reteretor, besign proposals to ediff or to deepon or plus back to a different reteretor, besign proposals to ediff or to deepon or plus back to a different reteretor, besign proposals to expense of the proposals to expense or proposals to ediff or to deepon or plus back to a different reteretor proposals to edifferent proposals to edifferent proposals to ediff or to deepon or plus back to a different reteretor proposals to edifferent propos | 7111000 | - Navajo Allotted |
| Ruby S. Well No. | | 7. UNIT AGREEMENT NAME |
| 1. oil Section Section | reservoir. Use Form 9-331-C for such proposals.) | 8. FARM OR LEASE NAME |
| J. Gregory Merrion & Robert L. Bayless 3. ADDRESS OF OPERATOR P.O. Box 507, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SUMFACE: 790 FNL & 1790 FWL AT TOP PROD. INTERVAL: same AT TOTAL DEPTH:_Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING NUTTHEE COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent of this work.)* 17. DESCRIBE PROPOSED O | =- =-: | T(U)y |
| 3. ADDRESS OF OPERATOR P.O. BOX 507, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 790 FNL & 1790 FWL AT TOP PRODI INTERVAL: same AT TOTAL DEPTH-Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CHANGE ZONES ABANDON* (other) Drilling Operations X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. The POPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 19. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all pertinent details, and give pertinent dates, including estimated date of sta | 2. NAME OF OPERATOR | T 1 사용한 회 활동 |
| 3. ADDRESS OF OPERATOR P.O. BOX 507, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below) AT SURFACE: 790 FNL & 1790 FWL AT TOP PROD. INTERVAL: same AT TOTAL OEPTH-same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CHANGE ZONES ABANDON* (other) Drilling Operations X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. LEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. (NOTE Report results of multiple completion or zone change on form 9-330.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Report results of multiple completion or zone change on form 9-340.) (NOTE Repor | J. Gregory Merrion & Robert L. Bayless | 10. FIELD OR WILDCAT NAME = # 2 |
| AREA Section 34, T26N, R12W Section 34, T26N, R12W Section 34, T26N, R12W Section 34, T26N, R12W AT TOP PROD. INTERVAL: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CHANGE ZONES ABANDON* Drilling Operations X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and frue vertical depths for all markers and zones pertinent to this work.)* 02-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 1b/ft surface casing with 30 sacks cement. 02-21-80 TD @ 1300 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron log: Preparing to run casing. DED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBID 1274.6 ft. G.R. Bumpot 150. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is rue and correct SIGNED *** TITLE **Engineer** ITILE **Engineer** ITILE **Engineer** PARE** Section 34, T26N, R12W San Juan 10. APINO. 10. APINO. | | WAW Fruitland Pictured Cliffs |
| AREA Section 34, T26N, R12W 12. COUNTY OR PARISH 13. STATE SAN JUAN New Mexico 14. API NO. 15. ELEVATIONS (SHOW OF, KDB, AND WD) 6178 ft. G.L. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CHANGE ZONES ABANDON* (other) Drilling Operations 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 02-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 02-21-80 TD @ 1300 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron log: Preparing to run casing. IDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBID 1274.6 ft. G.R. Bumps 1230 The part of the p | • | 11. SEC., T., R., M., OR BLK. AND SURVEY OR |
| Section 34, T26N, RIZW AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF | | 7 AREA 원호주 등 일을™을 |
| AT SURFACE: 790 FNL & 1790 FWL AT 107 PROD. INTERVAL: Same AT 10TAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CHANGE ZONES ABANDON* (other) Drilling Operations T. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. DEDC REPORT OF PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work if well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 10. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including the pertinent details, a | • | |
| AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING CHEETE CHANGE ZONES ABANDON* (other) Drilling Operations 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 19. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, charge on Form 9-330.) 19. DEDET REPAIR WELL 19. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, charge on Form 9-330.) 19. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, charge on Form 9-330.) 19. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state | | 12. COUNTY OR PARISH 13. STATE |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 17. ENDEDD**02-25-80 18. I hereby ceriffy that the foregoing is true and correct SIGNED 19. Inter Englan Wall (Page 10 1274.6 ft. G.R. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 17. ELEVATIONS (SHOW DF, KDB, AND WD) 18. I hereby ceriffy that the foregoing is true and correct SIGNED 18. I hereby ceriffy that the foregoing is true and correct SIGNED 19. SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 15. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 16. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 16. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 16. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 16. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 16. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 16. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 16. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 16. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 16. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 17. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 18. ELEVATIONS (SHOW DF, KDB, AND WD) 6178 ft. G.L. 18. I hereby ceriffy that the foregoing is true and correct SIGNED | AT TOP PROD. INTERVAL: same | San Juan New Mexico |
| REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Drilling Operations T. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. Described Proposed Well and a starting any proposed work. If well is directionally drilled, give subsurface locations and measured with and give pertinent dates, including estimated date of starting and give pertinent dates. 19. DEDATE REPAIR WELL (NOTE Report results of multiple completion or zone change on Form 9-330.) (NOTE Report results of multiple completion or zone change on Form 9-330.) (NOTE Report results of multiple completion or zone change on Form 9-330.) (NOTE REPAIR WELL (NOTE Report results of multiple completion or zone c | AT TOTAL DEPTH: same | 14. API NO. 2555 2 5236 |
| REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. Describe Proposed Or Complete Doperations 19. Describe Proposed Or Complete Complete Doperations 19. Describe Proposed Or Complete Complete Complete Or Complete Doperations 19. Describe Proposed Or Complete Complet | | F, <u></u> |
| TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Drilling Operations To ESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 02-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 02-21-80 Drilling at 400 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron log: Preparing to run casing. IDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9,9 gallons/sk, yielding 1.18 sx.) Compensated Density-Neutron log: Cement back to surface. PBID 1274.6 ft. G.R. Bumper 1:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is frue and correct SIGNED (This space for Federal or State office use) | REPORT, OR OTHER DATA | |
| TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Drilling Operations I. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 02-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 02-21-80 Drilling at 400 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Incuction, Compensated Density-Neutron log: Preparing to run casing. DED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumpo 11:30 p.m. WCC. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is rue and correct SIGNED TITLE Engineer DATE February 276,N.980 (This space for Federal or State office use) | DEGLEST FOR ARRESTAL TO: CURSONELL REPORT OF | 6178 ft. G.L. |
| FRACTURE TREAT SHOOT OR ACIDIZE SHOOT OR ACIDIZE PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Drilling Operations X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 02-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 02-21-80 Drilling at 400 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron log. Preparing to run casing. Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumpo 1130 p.m. WCC. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Engineer (This space for Federal or State office use) | | 도로 보고 있는 사람들은 사람들이 되었다. Hand Hand Hand Hand Hand Hand Hand Hand |
| SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLÉTE CHANGE ZONES ABANDON* (other) Drilling Operations X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 02-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 02-21-80 Drilling at 400 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron log: Preparing to run casing. IDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumps 1.30 p.m. WCC. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is rue and correct SIGNED TITLE Engineer DATE February 27, N1980 (This space for Federal or State office use) | F | |
| PULL OR ALTER CASING MULTIPLE COMPLÉTE CHANGE ZONES ABANDON* (other) Drilling Operations X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 02-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 02-21-80 Drilling at 400 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron log. Preparing to run casing. NDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumper 1:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is rue and correct SIGNED THE Engineer DATE February 27, 11.980 | | |
| MULTPLE COMPLETE CHANGE ZONES ABANDON* (other) Drilling Operations 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 18. O2-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 19. O2-21-80 Drilling at 400 ft. 19. O2-22-80 TD @ 1300 ft. 19. O2-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron log: Preparing to run casing. 19. Preparing to run casing. 19. Spid up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBID 1274.6 ft. G.R. Bumper 1:30 p.m. WCC. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Engineer DATE February 27, 11980 (This space for Federal or State office use) | REPAIR WELL | |
| CHANGE ZONES ABANDON* (other) Drilling Operations X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* O2-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. O2-21-80 Drilling at 400 ft. O2-22-80 TD @ 1300 ft. O2-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron loggen Preparing to run casing. DED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumps 11:30 p.m. WCC. Subsurface Safety Valve: Manu. and Type 18. I hereby cerify that the foregoing is rue and correct SIGNED TITLE Engineer OATE February 27 (N1980) (This space for Federal or State office use) | | change on Form 9-330.) |
| ABANDON* (other) Drilling Operations X 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 102-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 102-21-80 Drilling at 400 ft. 102-22-80 TD @ 1300 ft. 102-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron logs Preparing to run casing. 10ED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumps 11:30 p.m. WCC. Subsurface Safety Valve: Manu. and Type 11:11LE Engineer PATE February 27, N.1980 [Ft. Chis space for Federal or State office use) | | |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 02-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 02-21-80 Drilling at 400 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron logs. Preparing to run casing. NDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumpet 1:30 p.m. WCC. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED ITTLE Engineer (This space for Federal or State office use) | | |
| including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 02-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 02-21-80 Drilling at 400 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron logs Preparing to run casing. NDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumps 1:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type ITTLE Engineer ITTLE Engineer DATE February 276,1980 (This space for Federal or State office use) | | |
| including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 02-20-80 Rig up L & B Speed Drill on 2-19-80. Spud 9-3/4" hole to 102 ft.; ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 02-21-80 Drilling at 400 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron logs Preparing to run casing. NDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumps 1:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type ITTLE Engineer ITTLE Engineer DATE February 276,1980 (This space for Federal or State office use) | | · |
| ran 101.5 ft. of 7", 23 lb/ft surface casing with 30 sacks cement. 02-21-80 Drilling at 400 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron logs. Preparing to run casing. NDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBID 1274.6 ft. G.R. Bumper 11:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type INTLE Engineer INTLE Engineer Characterists with 30 sacks cement. February 27, N.980 | including estimated date of starting any proposed work. If well is | s directionally drilled, give subsurface locations and |
| 02-21-80 Drilling at 400 ft. 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron logs. Preparing to run casing. NDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumps 1:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type ITTLE Engineer OATE February 27, N.980 (This space for Federal or State office use) | 02-20-80 Rig up L & B Speed Drill on 2-19- ran 101.5 ft. of 7", 23 lb/ft sur | 80. Spud 9-3/4" hole to 102 ft.; face casing with 30 sacks cement. |
| 02-22-80 TD @ 1300 ft. 02-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron logs Preparing to run casing. NDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumps always 1:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type INTLE Engineer THE Engineer THE DATE OATE | | |
| O2-23-80 Rig up Birdwell, ran IES Induction, Compensated Density-Neutron logs Preparing to run casing. Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumper The Use of the Compensated Density-Neutron logs Subsurface Safety Valve: Manu. and Type TITLE Engineer TITLE Engineer TITLE Engineer TITLE Engineer TITLE Engineer TITLE DATE February 27, N.980 THE DATE February 27, N.980 | 02-22-80 TD @ 1300 ft. | 医克雷氏征 电电子电子 医电子 |
| Preparing to run casing. Ran 57 joints 2-7/8", EUE, C-45, yellow band casing and landed at 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofill (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumpe 1130 p.m. WOC. Subsurface Safety Valve: Manu. and Type INTLE Engineer TITLE Engineer THE February 27 N.980 THE February 27 N.980 | 02-23-80 Rig up Birdwell, ran IES Inductio | n, Compensated Density-Neutron logs |
| 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofili (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBID 1274.6 ft. G.R. Bumped allow 1:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type TITLE Engineer (This space for Federal or State office use) DATE PATE PATE PATE PATE PATE | Preparing to run casing. | |
| 1298.5 ft. G.R. Rigged up National & cemented with 80 sx Econofili (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neat (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBID 1274.6 ft. G.R. Bumped allow 1:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type TITLE Engineer (This space for Federal or State office use) DATE PATE PATE PATE PATE PATE | NDED**02-25-80 Ran 57 joints 2-7/8", EUE, C-45, | yellow band casing and landed at |
| (9.9 gallons/sk. yielding 1.64 sx.) and 50 sx neaf (5.2 gallons/sk. yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumped allow 1:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Engineer (This space for Federal or State office use) | 1298.5 ft. G.R. Rigged up Nation | al & cemented with 80 sx Econofill |
| yielding 1.18 sx.) Good returns throughout. Circulated 5 sx. cement back to surface. PBTD 1274.6 ft. G.R. Bumpet 11:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED | (9.9 gallons/sk. yielding 1.64 sx | and 50 sx neat (5.2 gallons/sk. |
| Cement back to surface. PBTD 1274.6 ft. G.R. Bumpetalia 1:30 p.m. WOC. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Engineer (This space for Federal or State office use) DATE DATE DATE | yielding 1.18 sx.) Good returns | throughout. Circulated 5 sx. |
| Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Engineer (This space for Federal or State office use) DATE DATE | cement back to surface. PBTD 127 | 4.6 ft. G.R. Bumped alva 31:30 |
| 18. I hereby certify that the foregoing is true and correct SIGNED | | /CHAD |
| SIGNED TITLE Engineer DATE February 27, N.980 (This space for Federal or State office use) | Subsurface Safety Valve: Manu. and Type | |
| (This space for Federal or State office use) | | |
| TITLE DATE | SIGNED Sturn Souling IITLE Engineer | DATE FEDILIARY 240130 |
| APPROVED BY TITLE DATE | (This space for Federal or State | office use) |
| | APPROVED BY TITLE | DATE ACCEPTED FOR RECO |

*See Instructions on Reverse Side