5. LEASE

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

DEPARTMENT OF THE INTERIOR	NOO-C-14-20-/480= % 6 =
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	NAVAJO, BANTO SO SELO
COMPRES NOTICES AND DEPONTS ON MELLS	7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. 5777 AGAZEMENT ATAMET SEE
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	# 2 = 1
	8. FARM OR LEASE NAME 2 24 8
1. oil 🖂 gas 🔽	DOME NAVAJO 24-26-13: 5 =
well well other	9. WELL NO. 유무증권 # 휴대한
2. NAME OF OPERATOR	4 2 5
DOME PETROLEUM CORPORATION	10. FIELD OR WILDCAT NAME
	WAW FRUITLAND-PICTURED CLIFF
	<u> </u>
Suite 107, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 원일 취임 이 기원 기원
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	T
below.)	SEC. 24, T26N, R13W
AT SURFACE: 810 FNL, <del>901</del> ' FWL	12. COUNTY OR PARISH 13 STATE
AT TOP PROD. INTERVAL:	SAN JUAN FE NEW MEXICO
AT TOTAL DEPTH:	14. API NO. = = = = = = = = = = = = = = = = = = =
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DE KDB, AND WD)
112. 41., 41. 41.	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6041 GR 설립도 및 경험적
TEST WATER SHUT-OFF	සැ <u>වීම්මී මේ කි</u> ම්මීම
FRACTURE TREAT	4 E B A C E B B B B B B B B B B B B B B B B B B
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.) The Example completion of 2016
MULTIPLE COMPLETE	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
CHANGE ZONES	Rodica to the product of the product
ABANDON*	
(other) RUN PRODUCTION CASING	그 그는 전 기회회회회 회 활 문화사용 사회의
	ଅନ୍ତିକ୍ତି ଓ ଜିଲ୍ଲିଆ 🚉
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates,	
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and	
measured and true vertical depths for all markers and zones pertinent to this work.)*	
Ran 42 jts (1259') 2 7/8", 6.5#, J-55 EUE cas	
Cemented with 100 sacks 65/35/ Pozmix, 1/4# Floseal/sk, & 10# Gilsonite/sk.	
Followed with 50 sacks class "B" cement with 2% CaCl, 1/4# Floseal/sk, & -	
10# Gilsonite/sk. Plug down at 5:15 P.M., 12/03/79. Circulated cement:	
्राप्त के प्रमुख के स्वर्ण के इस्त्रिक स्वर्ण के स	
	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
Ta ling the condition of the condition o	
	医二甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基
	edus tol les Clempal de Clempal de Clempal de Marchine Ma
	요청하였 중시원 없는 최상교회 : 100
	At less A do En la Entre Man Man Dogum Laboration
	후불리로함 집황 점획으로
Subsurface Safety Valve: Manu. and Type	Ft.
19. Thereby contifue that the foregoing is true and correct	
18. I hereby certify that the foregoing is true and correct	ខ្នុំគ្នាស្ថា ភូមិ សុទ្ធិ
SIGNED SUBSCIENCES SIGNED STILLE DRLG & PROD FO	OREMAN December 4, 1979
H. D. HOLAINGSWORTH	
(This space for Federal or State of	fice use) - 문용량당실 실육 원종일본
ADDDOVED BY	DATE A DED DE A VELO
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE APERIO VIED
ารากาณ	ने होते हैं। संदेश के प्रसिद्ध के स्ट्रिक्ट के
	ENDING TO TAKE OF THE
	0 1 1 2 70 1

\*See Instructions on Reverse Side

JAMES F. SIMS DISTRICT OIL & GAS SUPERVISOR