

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
J. Gregory Merrion & Robert L. Bayless

3. ADDRESS OF OPERATOR
P.O. Box 1541, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1900 FSL & 790 FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
SF-080238-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Chaco

9. WELL NO.
13

10. FIELD OR WILDCAT NAME
WAW Fruitland/Pic. Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 10, T26N, R13W

12. COUNTY OR PARISH
San Juan

13. STATE
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	☐	☐
FRACTURE TREAT	☐	☒
SHOOT OR ACIDIZE	☐	☒
REPAIR WELL	☐	☐
PULL OR ALTER CASING	☐	☐
MULTIPLE COMPLETE	☐	☐
CHANGE ZONES	☐	☐
ABANDON*	☐	☐
(other) Spud to completion	☐	☒

RECEIVED

AUG 21 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

1980: Report results of multiple completion or change on Form 9-330.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

04-03-80 Spud 9-3/4" hole to 99 ft. Set 98 ft. of 7", 23# surface casing with 50 sacks 3% CACL₂.

04-04-80 Drilled out from under surface; drilling @ 600'.

04-07-80 Drilled to TD @ 1385'. Laid down drill pipe.

04-08-80 Ran IES Induction & Compensated Neutron Density logs. Prep. to run casing.

04-09-80 Ran 2-7/8", EUE, 10V, 6.5#, yellow band casing and landed @ 1382'. PBTD @ 1358'. Cemented with 125 sacks econofill followed by 50 sacks

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Engineer DATE 08-19-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
AUG 22 1980
FARMINGTON DISTRICT

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

Class "B" neat. Circulated cement to surface.

07-14-80 Ran Gamma Ray Collar log from TD to 800'. Pressure tested to 3500 psig, held 10 minutes. Perforated Pictured Cliffs 1327-30' (4 holes). Broke down with water. Perforated 1310-22 (12 holes). Foam frac with 15,000# 10/20 sand @ 15 BPM. Left blowing to atmosphere.

07-17-80 Tested 9 lbs. on 3/4" plate - 245 MCF/day. Shut in waiting on pipeline connection.