

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other2. NAME OF OPERATOR
Jerome P. McHugh3. ADDRESS OF OPERATOR
Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 790' FSL - 790' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐5. LEASE
NM 16471
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Bengal B
9. WELL NO.
#6
10. FIELD OR WILDCAT NAME
South Gallegos FR PC
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 2 T26N R12W
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5926' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. Spudded 8-3/4" hole @ 10:00 a.m. 2-5-80. Drilled to 92'.
-
- Ran 2 jts 7" OD 23# 8R "B" condition csg. TE 91.30' set @ 92' GL.
-
- Cemented w/50 sx neat. POB @ 2:00 p.m. 2-5-80. Cement circulated.

Depth 640'. Drilled to 640'. Started circulating around outside of surface csg. Attempted to re-cement surface csg. Found surface pipe parted one joint down. 2-7-80

Screwed into surface csg. Pulled csg and peened collar on first joint, re-ran csg. Added 6.67' of 7" casing. Re-cemented w/50 sx class "B" w/2% CaCl. Good cement to surface. POB @ 3:30 p.m. 2-8-80.

Ran 46 jts 2-7/8" OD 6.4# CW-55 10R NEUE tbq for csg. TE 1357.33' set @ 1357' GL. Had good circulation and reciprocated pipe while cementing. Cemented w/75 sx 2% Lodense w/1/4# cello flake per sx followed by 50 sx neat w/1/4# cello flake per sx. Total slurry 214 cu ft. Bumped plug w/1500 psi. Released to 750 psi. Shut in.

Sul
18

POB 1:50 p.m. 2-11-80.

SIGNED Jim L. Jacobs TITLE Agent DATE 2-12-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

