

5-USGS (Farmington) 1-Tully 1-File

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other2. NAME OF OPERATOR  
Dugan Production Corp.3. ADDRESS OF OPERATOR  
Box 208, Farmington, NM 874014. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1850' FNL - 1850' FEL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) ☐

5. LEASE

NM 37912

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

King Fish

9. WELL NO.

#1

10. FIELD OR WILDCAT NAME

WAW Fruitland PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 3 T26N R13W

12. COUNTY OR PARISH

San Juan

13. STATE


NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6108' GL

(NOTE: Report results of multiple completion zones change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-12-80

Moved in and rigged up Morrow Drlg rig. Spudded 8-3/4" hole @ 9:30 a.m.

5-12-80. Drlg to 81'. Ran 2 jts 7" OD 23# 8R "B" condition casing. TE

80.78' set @ 80' GL. Cemented w/35 sx class "B". Good cement to surface.

POB @ 12:30 p.m. 5-12-80.

5-16-80

Laid down drill pipe. Rigged up and ran 48 jts 2-7/8" OD 6.5# 8R EUE tbg

for csg. TE 1417.45' set @ 1416' GL. Cemented w/75 3/4" x 2" lodense w/1/4#

cello flake per sx followed by 50 sx class "B" w/1/4# cel to flake per sx.

Good cement to surface. POB @ 12:00 noon 5-16-80. Estimated cement top

50'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist DATE 5-30-80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

NMCCO

ACCEPTED FOR RECORD

JUN 3 1980

FARMINGTON DISTRICT