## STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

RECEIVED

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leskage tests 20% t 0 1991

packer les	or reporting ikage tests t New Mexico	NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST WESTERN REGION						
tor <u>H</u>	alluved		Lease		N	Vell State 16-		
on Uk Unit	Sec. 16	1wp. 26 N	Rge	8 W	County _	San Joun		
NAME OF RESERVOIR OR POOL  per plotion P C  were plotion D alutu			TYPE OF PRO (OH or Gos	DD. M	ETHOD OF PROD. (Flow or Art Lift)	TBG		
			aus		7 low			
			gas		7 low 7 low			
		PRE-FLC	W SHUT-IN PR			red? (Yes or No)		
Hour, gate t	shut-in	Length of time shu	C-911	Si press. psig	i			
etion: 5 2 8 9 1 Page 1			I-In 6	Si press. psig	Stabili	Stabilized? (Fes or No)		
Hour, date t	shut-in	3 1	· · ·	651		yus		
Closi.			FLOW TEST !					
	- A- A- B-		TEOW TEST	Zone producing (U	pper er Lowerk			
TIME (hour, date)	LAPSED TIME SINCE*	Upper Completion	SURE   7 3	PROD. ZONE TEMP.		REMARKS		
	1 24	172	410					
	48	187	651					
	73	187	651		turnel la	we you on		
	96	187	176					
	120	187	176					
	144	187	176		turned a	April John Ton		
duction rate	during test							
:	20	PD based on	Bbls. i	n Hou	irs Grav	GOR		
			FPD; Tested thr					
s:			FEST SHUT-IN			*		
		MID-		SI press. psig	Sta	bilized? (Yes or No)		
	ta shiildh		_	+				
Hour, da Japer naietion		!		SI press. paig	Sta	bilized? (Yes or No)		

JUN 2 4 1991

(Continue on reverse side)

FLOW TEST NO. 2

Zone producing (Upper or Lower):

	LAPSED TIME	rnes	BURE	PROD. ZONE	
TIME (hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS
		<u>:</u> -:		<u></u>	
		; <b>!</b>			
	·	<del> </del>		<del></del>	······································
			ļ		
<del></del>	<del> </del>		<b></b>		
• • • • • • • • • • • • • • • • • • • •				•	
	ĺ				
	1		L		
		MCFF	PD: Tested thru (	Orifice or Meter):	
rks.					
rks:	, , , , , , , , , , , , , , , , , , ,				
rks:					
				nplete to the best of n	_
by certify th	oat the informatio	on herein containe			_
by certify th	oat the informatio	on herein containe			_
by certify the	nat the information	on herein containe			_
by certify the	IN 2 4 1991	on herein containe	_ 19 Op By	perator <u>Nallw</u>	d Petroleum,
by certify the	IN 2 4 1991	on herein containe	_ 19 Op By	perator <u>Nallw</u>	_
by certify the oved	IN 2 4 1991	on herein containe  ivision  ARLES GHOLSON	_ 19 Op By Tit	perator <u>Nallw</u>	d Petroleum,

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date) ##

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall tenaits sharely with the some which has produced.
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a dead-reight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leskage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).