Form 9-331 Dec. 1973

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES ABANDON* (other)

Form Approved

*(NOTE: Report results of multiple completion

OIL COM. COM.

change on

Form 9–331 Dec. 1973	Budget Bureau No. 42-R1424			
UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE NM 02874-A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME Huerfano Unit 8. FARM OR LEASE NAME			
1. oil gas X other	Huerfano Unit 9. WELL NO.			
2. NAME OF OPERATOR El Paso Natural Gas Company	177R 10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, NM	Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 900'S, 1640'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	AREA Sec. 22, T-26-N, R-10-W NMPN 12. COUNTY OR PARISH 13. STATE San Juan New Mexico 14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SUBSEQUENT REPORT OF:

10-18-80: TD 6867'. Ran 167 joints 4 1/2", 10.5#, K-55 production casing 685 set 6867'. Float collar set at 6850', stage tools set at 5101-2276' Cemented 1st stage w/ 389 cu. ft. cement, 2nd stage w/ 555 cu. ft. cement, 3rd stage w/ 464 cu. ft. cement. WOC 18 hours. Top of cement at 2000'. PBTD 6850'. Tested casing to 4000#, OK. Perfed: 11-9-80: 6644,6650,6656,6662,6668,6674,6680' W/1 SPZ. Fraced w/ 51,700# 20/4 sand, 44,600 gal. wtr. Flushed w/ 4000 gal.wtr.

Subsurface Safety Valve: Manu. and Type			Set @	· -	Ft.
19 I haraby certify that the foregoing is to	rue and correct			• •	-
SIGNED A. Susco	TITLE Drilling Clerk	DATE _	November	12,	1980
	(This space for Federal or State office use)				
APPROVED BY	TITLE	DATE	<u> </u>	1	

