

2 UGSG, Fmn 1 McHugh
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY1 File
SUBMIT IN DUPLICATE*(See other in-
structions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:		OIL WELL ☐	GAS WELL ☐	DRY ☒	Other ☐										
b. TYPE OF COMPLETION:		NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF. RESVR. ☐	Other ☐								
2. NAME OF OPERATOR Jerome P. McHugh															
3. ADDRESS OF OPERATOR P O Box 208, Farmington, NM 87401															
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface 1850' FNL - 1850' FEL At top prod. interval reported below At total depth															
14. PERMIT NO. U. S. GEOLOGICAL SURVEY FARMINGTON, N. M. 15-20-80															
5. LEASE DESIGNATION AND SERIAL NO.		NM 26354													
6. IF INDIAN, ALLOTTEE OR TRIBE NAME															
7. UNIT AGREEMENT NAME															
8. FARM OR LEASE NAME		Chaco Plant													
9. WELL NO.		20R													
10. FIELD AND POOL, OR WILDCAT		WAW Fruitland PC													
11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA		Sec 27 T26N R12W													
12. COUNTY OR PARISH		San Juan				13. STATE NM									
15. DATE SPUDDED		16. DATE T.D. REACHED		17. DATE COMPL. (Ready to prod.)		18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*		19. ELEV. CASINGHEAD							
5-6-80		5-9-80		12-3-81 P & A		6138' GL									
20. TOTAL DEPTH, MD & TVD		21. PLUG, BACK T.D., MD & TVD		22. IF MULTIPLE COMPL., HOW MANY*		23. INTERVALS DRILLED BY		ROTARY TOOLS CABLE TOOLS							
1250'		1198'		NA		TD									
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* NA								25. WAS DIRECTIONAL SURVEY MADE NO							
26. TYPE ELECTRIC AND OTHER LOGS RUN SP, gamma ray, resistivity, density, GR-CCL								27. WAS WELL CORED NO							
28. CASING RECORD (Report all strings set in well)															
CASING SIZE		WEIGHT, LB./FT.		DEPTH SET (MD)		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED					
7"		23		885 GL		8-3/4"		35 sx class B neat		---					
2-7/8"		6.4		1232' GL		5"		75 sx 2% Iodense w/ 1/4# celloflake + 50 sx class B w/ 1/4# celloflake		---					
29. LINER RECORD										30. TUBING RECORD					
SIZE		TOP (MD)		BOTTOM (MD)		SACKS CEMENT*		SCREEN (MD)		SIZE		DEPTH SET (MD)		PACKER SET (MD)	
None										None					
31. PERFORATION RECORD (Interval, size and number) 1156-1162', 6 holes 1166-1174', 8 holes										32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.					
										DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED			
										1156-1174'		250 gals 15% HCL w/ I-15			
33.* PRODUCTION															
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)						WELL STATUS (Producing or shut-in)							
NA P & A								shut-in)							
DATE OF TEST		HOURS TESTED		CHOKE SIZE		PROD'N. FOR TEST PERIOD		OIL—BBL.		GAS—MCF.		WATER—BBL.		GAS-OIL RATIO	
FLOW. TUBING PRESS.		CASING PRESSURE		CALCULATED 24-HOUR RATE		OIL—BBL.		GAS—MCF.		WATER—BBL.		OIL GRAVITY-API (CORR.)			
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)										TEST WITNESSED BY					
35. LIST OF ATTACHMENTS															
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records										ACCEPTED FOR RECORD					
SIGNED		Agent						DATE		1-20-82		JAN 20 1982			
Jim L. Jacobs															

*(See Instructions and Spaces for Additional Data on Reverse Side)

NMOCC

FARMINGTON DISTRICT
BY smn

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formations and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.
Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES			38. GEOLOGIC MARKERS			
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
				Kirtland Fruitland Pictured Cliffs	300' 650 1154	