

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR

Supron Energy Corp. c/o John H. Hill, et al.

3. ADDRESS OF OPERATOR Kysar Building, Suite 020
300 W. Arrington, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1045' FSL & 1215' FWL (SW/4)

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
OCT 22 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

NOTE: Report results of multiple completion or zone change on Form 9-339.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Total depth, 6 1/4" hole, drilled to 2356'.
2. Ran 76 joints (2353') of used 2 7/8", 6.5#, 8rd. EUE casing.
3. Set and cemented at 2353'.
4. Cemented with 400 sacks, Ideal Class B, 50/50 Pozmix, 6% gel, plus 1/2 cu/ft. or 3% Perlite. Tailed in with 150 sacks, Ideal Class B cement.
5. Bump Omega Latch-down type plug with 3000 PSI, 3:00 P.M., 7/5/80, released pressure. Omega plug latched down. Circulated 30 bbls. cement.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Norman I. Wells TITLE Superintendent DATE OCT 17 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NNMOCC