

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
Supron Energy Corp. c/o John H. Hill, et al.  
3. ADDRESS OF OPERATOR Kysar Building, Suite 020  
300 W. Arrington, Farmington, New Mexico 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1770' FNL & 860' FWL (SW NW)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF - 078432  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A  
7. UNIT AGREEMENT NAME  
N/A  
8. FARM OR LEASE NAME  
Hodges  
9. WELL NO.  
1-Y  
10. FIELD OR WILDCAT NAME  
Ballard Pictured Cliffs  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 21 T26N R8W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6397' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Total depth 6 1/4" hole, drilled to 2408'.
2. Ran 101 joints (2380') of used 2 7/8" 6.5#, J-55, 8RD. ST&C casing.
3. Set and cemented at 2380'.
4. Cemented with 400 sacks Ideal Class B, 50/50 Pozmix, 6% gel, 1/2 cu/ft. or 3% Perlite. Tailed in with 150 sacks Ideal Class B cement.
5. Bump Omega Latch-down type plug with 2500 PSI, 10:45 P.M., released pressure. Omega plug latched down, circulated 7 bbls. cement.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Bernard V. Waller TITLE Exploration and Development Superintendent DATE \_\_\_\_\_

OCT 17 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: