

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
Supron Energy Corp. c/o John H. Hill, et al.
3. ADDRESS OF OPERATOR Kysar Building, Suite 020  
300 W. Arrington, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 800' FNL & 1560' FEL (NW NE)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:


- ☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

OCT 25 1980

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



5. LEASE  
SF - 078384
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A
7. UNIT AGREEMENT NAME  
N/A
8. FARM OR LEASE NAME  
Newsom B
9. WELL NO.  
25
10. FIELD OR WILDCAT NAME  
Ballard Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 9 T26N R8W
12. COUNTY OR PARISH  
San Juan
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6800' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Spudded 10 3/4" hole, drilled to 300' at 6:00 A.M., 7/19/80, cement circulated.
2. Ran 7 joints (218') of New 7", 23# ST&C casing.
3. Set and cemented at 218'.
4. Cemented with 100 sacks, Ideal Class B, 3 sacks Calcium Chloride, 1 sack flo-cele.
5. Plug down at 3:15 P.M.
6. Circulation good throughout job. 15 bbls. cement circulated.
7. Checked water shut-off at 600# with 10", 900 Series Gardner-Denver Blow-out Preventer.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Thomas D. Wallis TITLE Exploration and Development Superintendent DATE OCT 17 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

171330