

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR

Supron Energy Corp. c/o John H. Hill, et al.

3. ADDRESS OF OPERATOR Kysar Building, Suite 020
300 W. Arrington, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 800' FNL & 1560' FEL (NW NE)

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
OCT 2 1980

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Total depth, 6 5/8" hole, drilled to 3000'.
2. Ran 114 joints (2976') of Used 2 7/8", 6.5#, 8RD, thread casing.
3. Set and cemented at 2976'.
4. Cemented with 400 sacks, Ideal Class B, 50/50 Pozmix, 6% gel, 1/2 cu/ft, per sack or 3% Perlite. Tailed in with 150 sacks, Ideal Class B cement.
5. Bump Omega Latch-down type plug with 2400 PSI, 7:15 A.M., 8/12/80, released pressure. Omega plug latched down. Circulated 10 bbls. cement.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Herman D. Wallis TITLE Exploration and Development Superintendent DATE OCT 17 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: