1a. TYPE OF WORK

b. TYPE OF WELL WELL 2. NAME OF OPERATOR

DRILL X

35 miles SE of Blanco, NM

(Also to nearest drig, unit line, if any)

18. DISTANCE FROM PROPOSED LOCATION*
TO NEAREST WILL, DRILLING, COMPLETED,
OR APPLIED FOR, IN THIS LEASE, FT.

21. ELEVATIONS (Show whether DF, RT, GR, etc.) 6838 GR

Z -2055 FSL & 1340 FEL At proposed prod. zone

15. DISTANCE FROM PROPUSED*
LOCATION TO NUAREST
PROPERTY OR LUASE LINE, FI

SUBMIT IN TRIPLICATE*

(Other instructions on

Form approved. Budget Bureau No. 42-R1425.

UNITED STATES DEPARTMENT OF THE INTERIOR

DEEPEN [

GEOLOGICAL SURVEY

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG

1340'

Supron Energy Corp. c/o Gordon L. Llewellyn

3. ADDRESS OF OPERATOR
Suite 14() Campbell Centre
8350 North Central Expressway, Dallas TX
4. LOCATION OF WELL (Report location clearly and in accordance with any State red
At Surface

1830/5 830/E

reverse Bide)	30-045-24440
	5. LEASE DESIGNATION AND SERIAL NO.
	SF-078431 0 8010
PLUG BACK	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	N/A
PLUG BACK 🗌	7. UNIT AGREEMENT NAME
Williams	N/A
MULTIPLE ZONE	S. FARM OR LEASE NAME
	Newsom
yn	9. WELL NO.
	#24
75206	10. FIELD AND POOL, OR WILDCAT
emants.	Blanco Mesa Verde
IVED	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
G (C)	Sec. 4 T26N R8W
	12. COUNTY OR PARISH 13. STATE
ica! sbevil/	San Juan NM
TO T	OF ACRES ASSIGNED THIS WELL
	160 -5 ==
РТН 20. пот	ARY OR CABLE TOOLS
	Do to wee
<u> </u>	22. APPROX. DATE WORK WILL START
	TART

June 15, 1980

23 PROPOSED CASING AND CEMENTING PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH QUANTITY OF CEMENT 12-½ m 8-5/8" new24#K-55ST&C 300' stage DV tool to cover 6-4" new 10.5#CW-55 5200' Pictured Cliffs ST&C

16. NO OF ACRES IN LEASE.

2291.93

19. PROPOSED DEPTH 5200'

- Drill 12- $\frac{1}{4}$ ' hole and set 8-5/8" surface casing to 300' with good returns Log F.O.P. checks in daily drill reports and drill $6-\frac{1}{4}$ ' hole to 5200'.
- Run tests if warranted and run 4½' casing if productive.
- Run logs, as needed, and perforate and stimulate as needed.

EXHIBITS ATTACHED) :	
"A" "B" "C" "D" "E" & "El" "F"	Location and Elevation Plat The Ten-Point Compliance Program The Blowout Preventer Diagram The Multi-Point Requirements for A.P.D. Access Road Maps to Location Radius Map of Field	
"G"	Drill Pad Layout, Production Facilities	& C
"H"	Cross-Section	

Drill Rig Layout IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal s to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any,

24. Engineer Drilling & Prod. (This space for Federal or State office use) PERMIT NO APPROVAL DATE APPROVED ATOMER AND COLLED ARE Dali daga SUBJECT TO GOME HAT SE WITH ATTACHED APPROVED BY A5 AMENDED CONDITIONS OF A PROVAL, IF ANY : "GENERAL REQUIREMENTS"

*See Instructions On Reverse Side

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

Form C=102 Supersedes C-128 Effective 1-1-65

All distances must be from the outer boundaries of the Section.

Supron	Energy C	orporation	Lease SF-0	7843	·	Well to. Newson #24			
Unit Letter	Section 42	Township 26 North			County San				
Actual Footage Loca		 			54"				
/830' feet from the SDUTA line and 830' feet from the EAST line Ground Level Elev. Producing Formation Pool Dedicated Acreage:									
6886	Ballare	d Pictured Cliff	Blance	o Meso	averde	320 - Acres			
1. Outline the acreage dedicated to the subject well by colored pencil or hachure marks on the plat below.									
2. If more th interest an	2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).								
		ifferent ownership is mitization, force-pool		e well, hav	ve the interes	ts of all owners been consoli-			
Yes	No If an	nswer is "yes;" type o	of consolidation		·				
		owners and tract desc	criptions which	have actua	ally been cons	solidated. (Use reverse side of			
	necessary.)	ed to the well until al	l interests have	hoon con	andidated (b.	communitization, unitization.			
						been approved by the Commis-			
sion.		· · · · · · · · · · · · · · · · · · ·							
	1		· i			CERTIFICATION			
			1		l he	reby certify that the information con-			
					1 1	ed herein is true and complete to the			
[1.			•	bes	of my knowledge and belief.			
	ľ		i		Namie				
	· + ·								
	1				Positi	on			
		·	1		Сопро	my			
					Date				
			, ! 	•					
									
	1		1		+ h	reby certify that the well location			
	1		1400	074		vn, on this plat was plotted from field s of actual surveys made by me or			
	1		I I	830	unde	r my supervision, and that the same			
	1		i		16 1	rue and correct to the best of my rledge and belief.			
 				 	-	HUDA			
	1			3	Date S	White A William Co.			
	i ,				8k	2 18 Exideresto			
	1		1		Regist on 4 or	Lun Surveyor			
	1		. I						
				1	G Count				
			7						

Form 9-331 (May 1963)	UNITED STA		SUBMIT IN TRIPLIC (Other instructions of Verse side)	n re _	Form approve Budget Burea DESIGNATION	d. u No. 42-R1424.
	GEOLOGICAL	SURVEY	-	SF-C	78431	SF-078436
(Do not use this for	RY NOTICES AND F m for proposals to drill or to o se "APPLICATION FOR PERMI	deepen or plug b	ack to a different reservoir.		DIAN, ALLOTTEE	OR TRIBE NAME
1. GAS TO				N/A	AGREEMENT NA	N E
2. NAME OF OPERATOR	OTHER			N/A 8. FARM	OR LEASE NAM	<u> </u>
Supron Eng.	rgy Corporation			News		
	c/o John Hill & Gor ee, Ste. 210, 17400 ort location clearly and in accor	rdon Llewe Dallas P dance with any	ellyn, The Lakes Parkway, Dallas, T State regulrements.	9. WELL X.75252 #	24 POOL, OR	WILDCAT
2055 FSI.	& 1340 FEL (NWSE)			11. SEC.,	CO Mesav	
1830/5	830/E					DOL
14. PERMIT NO.	15. ELEVATIONS (Show whether DF	RT, GR, etc.)		4 T26N TY OR PARISH Juan	
16.	Check Appropriate Box 1	To Indicate N	lature of Notice, Report,	or Other Date	a	
Y 0 T	ICE OF INTENTION TO:		st	UBSEQUENT REPOR	r or:	
TEST WATER SHUT-OFF	PULL OR ALTER CAS	INO	WATER SHUT-OFF		REPAIRING W	ELL
FRACTURE TREAT	MULTIPLE COMPLET	E	FRACTURE TREATMENT		ALTERING CA	SING
SHOOT OR ACIDIZE	ABANDON*		SHOOTING OR ACIDIZING	G	ABANDON MEN	т•
REPAIR WELL	CHANGE PLANS	X	(Other)			
(Other)				esults of multiple reompletion Repor		
	ocation was moved 1 sed is a new locati					
		-		O	REL.	
SIGNED AND	,	TITLEAg	Jent Consultant	DAT AS	TB 5-29-	80 ED DED
	*Se	ee Instructions	on Reverse Side	DIS	AMES F. SI	MEER

EXHIBIT "B"

TEN-POINT COMPLIANCE PROGRAM

OF NTL-6 APPROVAL OF OPERATIONS

Attached to Form 9-331C Supron Energy Corporation Newsom #24 NW SE Sec. 4 T26N R8W 2055'FSL & 1340'FEL San Juan County, New Mexico

The Geologic Surface Formation

The surface formation is the Wasatch.

Estimated Tops of Important Geologic Markers

Ojo Alamo	10/01
	1840'
Kirtland	2035'
Fruitland	25231
Pictured Cliffs	2733'
Chacra	3618'
Cliffhouse	4295'
Point Lookout	4975'
T 1 2 5	

Total Depth 5200'

3. Estimated Depths of Anticipated Water, Oil, Gas or Minerals

Ojo Alamo Kirtland Fruitland Pictured Cliffs Chacra Cliffhouse	1840' 2035' 2523' 2733' 3618' 4295'	Water Water Water Gas Water Gas
Point Lookout	4975'	Gas

4. The Proposed Casing Program

HOLE	INTERVAL	SECTION	SIZE	WEIGHT GRADE	NEW OR
SIZE		LENGTH	(OD)	& JOINT	USED
12-1/4"	0-300'	300 '	8-5/8"	24# K-55 ST&C	New
6-1/4"	0-5200'	5200'	4-1/2"	10.5# CW-55 ST&C	New

Cement Plans: 2 Stage - D.V. Tool to cover Pictured Cliffs

5. The Operator's Minimum Specifications for Pressure Control

 $\overline{\text{EXHIBIT "C"}}$ is a schematic diagram of the blowout preventer equipment. The BOP's will be hydraulically tested to half of working pressure after nippling up and after any use under pressure. Pipe rams will be operationally checked each 24-hour period, as will blind rams each time pipe is pulled out of the hole. Such checks of BOP will be noted on daily drilling reports.

Accessories to BOP will include a floor safety valve, drill string BOP and choke manifold with pressure rating equivalent to the BOP stack.

6. The Type and Characteristics of the Proposed Circulating Muds

Mud system will be fresh water gel with adequate stocks of sorptive agents on site to handle possible spills of fuel and oil on the surface. Heavier muds will be on location to be added if pressure requires.

DEPTH	TYPE	WEIGHT#/gal.	VISCOSITY-sec./qt.	FLUID LOSS cc		
0-300'	Natural Mud					
300-TD	Fresh Water Gel	8.4 - 9.5	35 - 45	less than 10		

7. The Auxiliary Equipment to be Used

- (a) No kelly cock will be used.
- (b) A float will be used at the bit.
- (c) Neither a mud logging unit nor a gas detecting device will be monitoring the system.
- (d) A stabbing valve will be on the floor to be stabbed into the drill pipe when kelly is not in the string.

8. The Testing, Logging and Coring Programs to be Followed

- (a) No DST's are anticipated.
- (b) The logging program will consist of an IES and a GR Density over selected intervals. Other logs will be determined at well site to best evaluate any shows.
- (c) No coring is anticipated.
- (d) Stimulation procedures will be determined after evaluation of logs. If treatment is indicated, appropriate Sundry Notice will be submitted.

9. Any Anticipated Abnormal Pressures or Temperatures

No abnormal pressures or temperatures have been noted or reported in wells drilled in the area nor at the depths anticipated in this well.

No hydrogen sulfide or other hazardous fluids or gases have been found, reported or known to exist at these depths in the area.

10. Anticipated Starting Date and Duration of the Operations

The anticipated starting date is set for June 15, 1980, or as soon as possible after examination and approval of drilling requirements. Operations should be completed within 10 days after spudding the well and drilling to casing point.




EXHIBIT "D"

MULTI-POINT REQUIREMENTS TO ACCOMPANY A.P.D.

Attached to Form 9-331C Supron Energy Corporation Newsom #24 NW SE Sec. 4 T26N R8W 2055' FSL & 1340' FEL San Juan County, New Mexico

Existing Roads

- A. The proposed well site and elevation plat is shown as EXHIBIT "A".
- B. From Blanco, New Mexico the distance is 35 miles. From Blanco Post Office proceed East on Highway #17 0.8 mile to Cutter Dam road and CR A-80; thence Southeast on CR A-80 3.8 miles to bridges; cross bridge continue Southeast 3.4 miles to CR A-58; thence South on CR-58 7.8 miles to East turn and low water crossing; cross river and continue South parallel to river 8.6 miles to NE-SE pipeline road; thence Southeast 1.3 miles; thence South 0.3 mile; thence Southeast 2.3 miles to top of Duffers Point; thence East 0.7 mile to fork; thence North-Northeast 6.7 miles, thence West 0.3 mile on proposed access road to location, as shown on EXHIBITS "E" & "E₁".
- C. All roads to location are color-coded on EXHIBITS "E" & "E $_1$ ". An access road 0.3 mile from the existing oil field road will be required, as shown on EXHIBITS "E" & "E $_1$ ".
- D. N/A
- E. This is a development well. All existing roads within a one-mile radius are shown on EXHIBIT "E".
- F. The existing roads need no improvement.

2. Planned Access Roads

Map showing all necessary access roads to be constructed or reconstructed is shown as $\frac{\text{EXHIBIT "E}_1"}{\text{EXHIBIT "E}_1"}$ for the following:

- (1) The maximum width of the running surface of the 0.3 mile of access road, extending beyond the existing oil field road will be 18'.
- (2) The grade will be 8% (eight percent) or less.

- (3) No turn outs are planned.
- (4) Appropriate water bars will be constructed to assure drainage off location to conform with the natural drainage pattern.
- (5) No culverts are needed. No major cuts or fills are anticipated along access road during drilling operation.
- (6) Surfacing materials will be native soil.
- (7) No gates, cattle guards, or fence cuts are needed.
- (8) The new access road to be constructed was staked and centerline flagged, as shown on EXHIBIT " E_1 ".

3. Location of Existing Wells

For all existing wells within a one mile radius of development well, see EXHIBIT "F".

- (1) There are no water wells within a one-mile radius of this location.
- (2) There are no abandoned wells in this one-mile radius.
- (3) There are no temporarily abandoned wells.
- (4) There are no disposal wells.
- (5) There are no wells presently being drilled.
- (6) There are 7 producing wells within this one-mile radius.
- (7) There are no shut-in wells.
- (8) There are no injection wells.
- (9) There are no monitoring or observation wells for other uses.

4. Location of Existing and/or Proposed Facilities

- A. Within a one-mile radius of location the following existing facilities are owned or controlled by lessee/operator:
 - (1) Tank Batteries: None
 - (2) Production Facilities: None
 - (3) Oil Gathering Lines: None
 - (4) Gas Gathering Lines: None
 - (5) Injection Lines: None
 - (6) Disposal Lines: None

- 3. If the well is productive, new facilities will be as follows:
 - (1) Production facilities will be located on the drill pad, as shown on EXHIBIT "G".
 - (2) All well flow lines will be buried and will be on the well site and battery site.
 - (3) Facilities will be 325 feet long and 160 feet wide.
 - (4) All construction materials for battery site and pad will be obtained from site. No additional material from outside sources is anticipated.
 - (5) Any necessary pits will be fenced and flagged to protect livestock and wildlife.
- C. Rehabilitation, whether well is productive or dry, will be made on all unused areas in accordance with B.L.M. stipulations.

5. Location and Type of Water Supply

- A. The source of water will be the San Juan River 26 miles North-Northwest of the location, as shown on EXHIBIT "E".
- B. Water will be transported by truck over existing roadways.
- C. No water well is to be drilled on this lease.

6. Construction Materials

- A. No construction materials are needed for drilling well or constructing access roads into the drilling location unless well is productive. The surface soil materials will be sufficient or will be purchased from Dirt Contractor as needed.
- B. No construction materials will be taken off Federal land.
- C. All surface soil materials for construction of access roads are sufficient.
- D. All major access roads presently exist as shown on EXHIBIT " E_1 ".

7. Handling of Waste Materials and Disposal

- (1) Drill cuttings will be buried in the reserve pit.
- (2) Drilling fluids will be handled in the reserve pit.

- (3) Any fluids produced during drilling test or while making production test will be collected in a test tank. If a test tank is not available during drilling, fluids will be handled in reserve pit. Any spills of oil, gas, salt water or other noxious fluids will be cleaned up and removed.
- (4) Chemical toilet facilities will be provided for human waste.
- (5) Garbage, waste, salts and other chemicals produced during drilling or testing will be handled in trash/burn pit. Drill fluids, water, drilling mud and tailings will be kept in reserve pit, as shown on EXHIBIT "H". The trash/burn pit will be totally enclosed with small mesh wire to prevent wind scattering trash before being burned or buried. Reserve pit will be fenced on three sides and the fourth side fenced upon removal of the rig.
- (6) After the rig moves out, all materials will be cleaned up and no adverse materials will be left on location. Any dangerous open pit will be fenced during drilling and kept closed until the pit has dried and is filled.

8. Ancillary Facilities

No air strip, camp or other facilities will be built during drilling of this well.

9. Well Site Layout

- (1) EXHIBIT "G" is the Drill Pad Layout as staked, with elevations, by Powers Elevation of Durango, Colorado. Cuts and fills have been drafted to visualize the planned cut across the location spot and the deepest part of the pad. Topsoil will be stockpiled per BLM specifications determined at time of pre-drill inspection.
- (2) EXHIBIT "H" is a plan diagram of the proposed rig and equipment, reserve pit, trash/burn pit, pipe racks and mud tanks. No permanent living facilities are planned. There will be a trailer on site.
- (3) EXHIBIT "G" is a diagram showing the proposed production facilities layout.
- (4) The reserve pits will not be lined.

10. Plans for Restoration

(1) Backfilling, leveling and contouring are planned as soon as all pits have dried. Waste disposal and spoils materials will be buried or hauled away immediately after drilling is completed. If production is obtained, the unused area will be restored as soon as possible.

- (2) The soil banked material will be spread over the area. Revegetation will be accomplished by planting mixed grasses as per formula provided by the BLM. Revegetation is recommended for road area, as well as around drill pad.
- (3) Three sides of the reserve pit will be fenced during drilling operations. Prior to rig release, the reserve pit will be fenced on the fourth side to prevent livestock or wildlife from becoming entrapped; and the fencing will be maintained until leveling and cleanup are accomplished.
- (4) If any oil is on the pits and is not immediately removed after operations cease, the pit containing the oil or other adverse substances will be flagged overhead or covered with wire mesh.
- (5) The rehabilitation operations will begin immediately after the drilling rig is removed. Removal of oil or other adverse substances will begin immediately or area will be flagged and fenced. Other cleanup will be done as needed. Planting and revegetation is considered best in Fall, 1981, unless requested otherwise.

11. Other Information

- (1) The soil is a sandy loam. The area is covered with cactus, sagebrush, cheat grass, native grass, juniper, cedar and pinon. There are livestock, rabbits and deer in the area. The topography is benched falling dramatically Westerly.
- (2) The primary surface use is for grazing. The surface is owned by the U.S. Government.
- (3) The closest live water is the San Juan River 27 miles North-Northwest as shown on <u>EXHIBIT</u> "E".
 - The closest occupied dwelling is located 6 miles West of site along Blanco Canyon, as shown on $\underline{\sf EXHIBIT}$ "E".
 - There are no known archaeological, historical, or cultural heritages that will be disturbed by this drilling.
- (4) There are no reported restrictions or reservations noted on the oil and gas lease.
- (5) Drilling is planned for on or about June 15, 1980. It is anticipated that the casing point will be reached within 10 days after commencement of drilling.

12. Lessee's or Operator's Representative

George Lapaseotes
Agent Consultant for
Supron Energy Corporation
600 South Cherry Street
Suite 1201
Denver, Colorado 80222
Phone (303) 321-2217

Jerry L. Lee Supron Energy Corporation c/o Gordon L. Llewellyn Suite 140 Campbell Centre 8350 North Central Expressway Dallas, Texas 75206 Phone (214) 692-7021

13. Certification


I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which presently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and, that the work associated with the operations proposed herein will be performed by Supron Energy Corporation and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved.


5-15-80

Date


George Lapaseotes Agent Consultant for

Supron Energy Corporation





0	\$ \\alpha \	\$	Φ	\$	\$	\$			Radius	llap of	Field	***
Ÿ	BLANCO.	·	❖	요 유	Φ		☆ ©	\$ \$ \$\$;	4	***		
 خ		₹ F	и ф	₽	\$	❖		\$	*	~ •	*	**
		Ω Φ	₩	\$ \$	or or	mile	RADIUS		ф ° ф	‡	¢	\$
	φφα -61 /20	\$0 V., G. \$1 40'0 76'	CORP. ☆	25 13		❖		*	\$	莽	¢	*
	;;	**************************************	₩	**	, ¤ _{\$}	O (Newso	m #24	į	\$	-	\$	☆
	*	ķr \$ ÷		φ. \		*				. ☆		4-
	33 .	ζt	- Ø		64¢ \$ 239	φ 51′DF 95′	☆	*				€
	٥	希 森	₽	\$	❖	❖	☼		‡		‡	þ
}	D	Φ	\$	☆	₽		₽	☆	❖	\$	₽	
	٦	\$ \$	\$	\$	\$	\$	\$\$	*	*	*	*	*
<i>3</i>	, p	33	\$		\	\$	≴⊹	*		☆	\$ \$	‡
a ⊀k		₹≵	*	\$	*	¢	*	☆	*	\$	*	*
	Ω	; <u></u>	*	······································	∴ LEGE	ND			*	‡		
	, p	;\$ -\$-	O LOCATI DRY HO OIL WE ABAND)L E		带 OHL B 带 ABANI Ÿ GAS	GAS WELL DONED OIL B WELL DONED GAS		*	· •	☆	
		32		ULATION PO			A WELL	~		*	Strong and the Agency	*



Supron Energy Corporation Newsom #24

