

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

RECEIVED
MAY - 3 1999
OIL CON. DIV.
DIST. 3

APR 29 1999

1. Type of Well
Gas

5. Lease Number
SF-078622
6. If Indian, All. or
Tribe Name

2. Name of Operator
Lively Exploration

7. Unit Agreement Name

3. Address & Phone No. of Operator
c/o Hicks Oil & Gas, P. O. Drawer 3307 Farmington, NM 87499 505-327-4902

8. Well Name & Number
Lively #17E

4. Location of Well, Footage, Sec., T, R, M
2390' FNL and 1270' FEL Sec. 1, T-26-N, R-8-W, NMPM
H

9. API Well No.
30-045-24455

10. Field and Pool
Basin Dakota

11. County & State
San Juan, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

Lively Exploration, plugged and abandoned this well on March 31, 1999,
per the attached Plug and Abandonment Report.

14. I hereby certify that the foregoing is true and correct.

Signed

Jim Hicks

Title

Agent

Date

4-27-99

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

APR 29 1999

FARMINGTON FIELD OFFICE
BY

NMCCD

A - PLUS WELL SERVICE, INC.

P.O. BOX 1979
FARMINGTON, NM 87499
505-325-2627 • FAX: 505-325-1211

Lively Exploration Company
Lively #17E
2390' FNL and 1270' FEL Sec. 1, T-26-N, R-8-W
San Juan County, NM
SF-078622

Plug & Abandonment Report

Cementing Summary:

- Plug #1** with retainer at 6562', spot 12 sxs Class B cement above retainer to isolate Dakota perforations and cover top.
- Plug #2** with 13 sxs Class B cement inside casing from 5704' to 5535' to cover Gallup top.
- Plug #3** with 12 sxs Class B cement inside casing from 3863' to 3700' to cover Mesaverde top.
- Plug #4** with 27 sxs Class B cement inside casing from 2276' to 1917' to cover Pictured Cliffs and Fruitland tops.
- Plug #5** with 25 sxs Class B cement inside casing from 1659' to 1325' to cover Kirtland and Ojo Alamo tops.
- Plug #6** with 44 sxs Class B cement inside casing from 414' to surface, circulate 1 bbl good cement out casing valve.

Plugging Summary:

Notified BLM on 3/29/99

3-29-99 Road rig and equipment to location, spot. Wellhead not square, re-spot rig. RU rig and equipment. Slight blow on casing and no blow on tubing. ND wellhead and NU BOP, test. TOH and tally 209 joints 2-3/8" 4.7# tubing, total 6651'. TIH with 4-1/2" Downhole retainer and set at 6568'. Attempt to set retainer, will not set. TOH with retainer still on tubing. Shut in well and SDFD.

3-30-99 Safety Meeting. Service equipment while waiting on wireline truck. RU A-Plus wireline and set 4-1/2" PlugWell retainer at 6562'. TIH with tubing and tag retainer. Load casing with 105 bbls water and circulate clean. Pressure test 4-1/2" to 500#, held OK. Plug #1 with retainer at 6562', spot 12 sxs Class B cement above retainer to isolate Dakota perforations and cover top. TOH to 5704'. Plug #2 with 13 sxs Class B cement inside casing from 5704' to 5535' to cover Gallup top. TOH to 3863'. Plug #3 with 12 sxs Class B cement inside casing from 3863' to 3700' to cover Mesaverde top. TOH to 2276'. Plug #4 with 27 sxs Class B cement inside casing from 2276' to 1917' to cover Pictured Cliffs and Fruitland tops. TOH to 1659'. Plug #5 with 25 sxs Class B cement inside casing from 1659' to 1325' to cover Kirtland and Ojo Alamo tops. TOH to 414'. Load casing and establish circulation out casing with 5 bbls water. Plug #6 with 44 sxs Class B cement inside casing from 414' to surface, circulate 1 bbl good cement out casing valve. TOH and LD tubing. Shut in well and WOC. Partially RD. SDFD.

3-31-99 Safety Meeting. ND BOP and dig out wellhead. Cut off wellhead and found cement down 20' in 4-1/2" casing and 15' in 8-5/8" annulus. Mix 24 sxs Class B cement, fill casing and annulus, and then install P&A marker. SDFD.

K. Schneider, BLM representative was on location.

J. Hicks, Lively Representative was on location.

4-1-99 Safety Meeting. RD rig and cut off anchors. Move off location.