UNITED STATES

DEPARTMENT OF THE INTERIOR	5. LEASE
GEOLOGICAL SURVEY	SF - 078430 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)	N/A 7. UNIT AGREEMENT NAME N/A
1. oil gas X other	8. FARM OR LEASE NAME Nickson
2. NAME OF OPERATOR	9. WELL NO. 9-E
Supron Energy Corp. c/o John H. Hill, et al.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR Kysar Building, Suite 020	Basin Dakota
300 W. Arrington, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA
below.)	Sec. 14 T26N R8W
AT SURFACE: 1780' FNL & 990' FEL (SE NE) AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	San Juan New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6312' GL
PULL OR ALTER CASING	change on Form 9–330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent.)	rectionally grilled, give subsurface locations and
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di	all pertinent details, and give pertinent dates rectionally drilled, give subsurface locations and to this work.)* to 356'. 5 ST&C casing. Calcium Chloride,
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent Spudded 12 3/4" hole at 8:00 P.M., 11/26/80 Ran 8 joints (343') of new 8 5/8", 24#, K-5 Cemented with 250 sacks Class B cement, 2% ¼# Flo-cele per sack. Plug down at 9:00 A.M., 11/27/80. Circulates. Test water shut-off to 800# with 10", 900 Second Seco	to 356'. 5 ST&C casing. Calcium Chloride, ed 10 barrels cement. eries Shaffer Blow-out
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent Spudded 12 3/4" hole at 8:00 P.M., 11/26/80 Ran 8 joints (343') of new 8 5/8", 24#, K-5 Cemented with 250 sacks Class B cement, 2% ½# Flo-cele per sack. Plug down at 9:00 A.M., 11/27/80. Circulates. Test water shut-off to 800# with 10", 900 September. Subsurface Safety Valve: Manu. and Type I, hereby certify that the foregoing is true and correct 	to 356'. 5 ST&C casing. Calcium Chloride, ed 10 barrels cement. eries Shaffer Blow-out
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent Spudded 12 3/4" hole at 8:00 P.M., 11/26/80 Ran 8 joints (343') of new 8 5/8", 24#, K-5 Cemented with 250 sacks Class B cement, 2% ½# Flo-cele per sack. Plug down at 9:00 A.M., 11/27/80. Circulates. Test water shut-off to 800# with 10", 900 September. Subsurface Safety Valve: Manu. and Type I, hereby certify that the foregoing is true and correct 	to 356'. 5 ST&C casing. Calcium Chloride, ed 10 barrels cement. eries Shaffer Blow-out
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent 1. Spudded 12 3/4" hole at 8:00 P.M., 11/26/80 2. Ran 8 joints (343') of new 8 5/8", 24#, K-5 3. Cemented with 250 sacks Class B cement, 2% \(\frac{1}{4}\)# Flo-cele per sack. 4. Plug down at 9:00 A.M., 11/27/80. Circulate 5. Test water shut-off to 800# with 10", 900 September. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct Exploration and Signed A.M. Superintendent Superinte	all pertinent details, and give pertinent dates rectionally drilled, give subsurface locations and to this work.)* to 356'. 5 ST&C casing. Calcium Chloride, ed 10 barrels cement. eries Shaffer Blow-out Set @Ft nd Development DEC 3 1980
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent Spudded 12 3/4" hole at 8:00 P.M., 11/26/80 Ran 8 joints (343') of new 8 5/8", 24#, K-5 Cemented with 250 sacks Class B cement, 2% 4# Flo-cele per sack. Plug down at 9:00 A.M., 11/27/80. Circulation Test water shut-off to 800# with 10", 900 September. Subsurface Safety Valve: Manu. and Type I hereby certify that the foregoing is true and correct Exploration at Signed Manual Marities Superintendent 	all pertinent details, and give pertinent dates rectionally drilled, give subsurface locations and to this work.)* to 356'. 5 ST&C casing. Calcium Chloride, ed 10 barrels cement. eries Shaffer Blow-out Set @Ft nd Development

FARMINGTON DISTRICT