91 Tesi

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

I Ida maxico					11	
GRY RIC	Lick	Le2se	HodgEs	N	Vell lo. <u>15-E</u>	
	n 21 - 1/-	Pre 8	(~W	County	SAN JUAN	
Upper mpletion BALLARD DICTURE CLIFF			ROD. MI	ETHOD OF PROD.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
				(Flow or Art. Lift)	(Tog. or Cog.) (59. Tbg.	
				=100		
			1	10W		
		OW SHUT-IN P	RESSURE DATA			
Upper Hour, date shut-in Length of time shut-in			SI press. psig	1	Stabilized? (Yes or No)	
					Stabilized? (Yes or No)	
hut-in		Length of time shut-in		1	٧٥٥	
× 2-23-92	72 hrs.		509		/ 	
		FLOW TEST	NO. 1	1	WER	
(1001) 011)				per or converge and		
LAPSED TIME		Lower Completion	PROD. ZONE TEMP.		REMARKS	
		497			<u> </u>	
1 '	389	503				
′	389	507				
	389	393	45	1332 1332		
	789	419	45	UIL UIL	LIST. 2	
19 5475						
	<u> </u>					
luring test			_	•	COR	
ВОГ	PD based ony	Bbls.	in <u>48</u> Hour	s Grav.	GOR	
	міл-1	TEST SHUT-IN	PRESSURE DATA	<u> </u>	w as one or No.	
	•					
shut-in	Length of time s		SI press. psig	Stati	ilized? (Yes or No)	
	NAME OF RESERVO Rd D:cfure DAK Inut-in DAK Inut-in LAPSED TIME SINCE* 1 DAY 2 DAYS 3 DAYS 4 DAYS 5 DAYS Guring test 3 1 BOI	Sec. 27 Twp. 26 - N - NAME OF RESERVOIR OR POOL	Sec. 27 Twp. 26-N- Rgc. 2 NAME OF RESERVOIR OR POOL Rd D:cture ci: F: GAS PRE-FLOW SHUT-IN PRINTING Length of time shut-in Length of time shut-in 1000 TEST 10:40Am 2-23-92 FLOW TEST LAPSED TIME SINCE* Upper Completion 1 DAY 389 497 2 DAYS 389 503 3 DAYS 389 503 5 DAYS 389 393 5 DAYS 389 419 Curing test 2 BOPD based on Y2 Bbls. 1	Sec. 27 Twp. 26-N- Rge. 2-W TYPE OF PROD. (Oil or Gee) MAME OF RESERVOIR OR POOL PRE-FLOW SHUT-IN PRESSURE DATA SI press. psig 389 SI press. psig 509 FLOW TEST NO. 1 Langth of time shut-in 10:40AM 2-26-92 LAPSED TIME SINCE* Upper Completion LAPSED TIME SINCE* Upper Completion LAPSED TIME SINCE* PRESSURE PROD. ZONE TEMP. 1 DAY 289 497 2 DAYS 389 503 3 DAYS 389 507 4 DAYS 389 499 SUPPLY STANDARD 455 Curring test 2 BOPD based on 12 Bbls. in 48 Hour 128 MCFPD;-Tested thru (Orifice or Meter)	Sec. 27 Twp. 26-N- Rgc. 2-W County 2	

FLOW TEST NO. 2

mmenced at (hour, d	(ata) * *				
	T	F	Zone producing (Upper or Lower):		
	LAPSED TIME SINCE **	Upper Completion	Lower Completion	PROD. ZONE TEMP.	REMARKS
					į
	-				
	-				

	1				
duction rate d	luting test				
	ВОРГ	D based on	Bbls. in	Hours.	Grav GOR
·		MCFF	D: Tested thru (Orifice or Meter)	:
narks:					
				······································	
acabu acasifu sh	and the second				
neby tertify th	lat the information	n petein containe	d is true and con	iplete to the best	of my knowledge.
oroved	<u>MAR U9 19:</u>	92	19 0	nerator (A)	he Cilway
lew Mexico Oi	l Conservation Di	vision -		CIAIOI	Care in
01	1///	4//	Ву		
Got !	hirtes,	Sholson			
	•	,	de		
_ DEPUTY (OIL & GAS INSPECT	TOR, DIST. #3	2 /	- 0 -	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 3. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Ten 'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Proceedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut in while the zone which was previously shut in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).