UNITED STATES DEDARTMENT OF THE INTERIOR

UNITED STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	SF - 078432 6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
GEOLOGICAL SURVEY	N/A		
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME N/A		
eservoir. Use Form 9–331–C for such proposals.)	8. farm or lease name Hodges		
1. oil gas X other	9. WELL NO.		
2. NAME OF OPERATOR	#20		
Supron Energy Corp. c/o John H. Hill, et al.	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR Kysar Building, Suite 020	Ballard Pictured Cliffs		
300 W. Arrington, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
below.)	Sec. 34 T26N R8W		
AT SURFACE: 990' FNL & 820' FWL (NW NW)	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6617' GR		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF U			
REPAIR WELL	NOTE: Report results of multiple completion or zone change on Form 9–330.)		
PULL OR ALTER CASING	333		
CHANGE ZONES	U, '		
ABANDON*	HURCHTY		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	e all pertinent details and give pertinent dates.		
including estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertinent	firectionally grilled, give subsurface locations and		
measured and true vertical depths for all markers and zones pertine	of the state of th		
1. Logged well, ran Gamma Ray and Neutron logs.			
 Perforated Pictured Cliffs, 2342, 46, 66, 82, 84, 86, 88, 90, 94 - 2402, 04. Total of 12 holes. 70 Quality Foam Frac, 1# sand for 36 barrels, 2# sand for 			
		147 barrels. 4. Frac with 34,965# 10/20 frac sand, 7497 gal	lons 1% KCl
		water and 205,700 cuft. Nitrogen.	
5. Maximum Pressure 2400#, 15 minute Shut-In Pressure 1250#. 5. 1250 1250 1250 1250 1250 1250 1250 1250			
Job complete 11/1/80.	A Company of the Comp		
Subsurface Safety Valve: Manu. and Type	Set @ Ft.		
18. I hereby certify that the foregoing is true and correct	alanment NOV 4 1980		
STORED WINNING WILLIAM TITLE Superintender	elopment		
(This space for Federal or State of			
APPROVED BY TITLE	DATE		
CONDITIONS OF APPROVAL, IF ANY:			