

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other ☐

2. NAME OF OPERATOR  
Supron Energy Corp. % John H. Hill, et al

3. ADDRESS OF OPERATOR Suite 020, Kysar Building  
300 W. Arrington. Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1850' FSL & 790' FWL (NW SW)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Squeeze Mesa Verde Zone ☒

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF - 078384

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
N/A

7. UNIT AGREEMENT NAME  
N/A

8. FARM OR LEASE NAME  
Newsom "B"

9. WELL NO.  
20

10. FIELD OR WILDCAT NAME  
Ballard Pictured Cliffs/Blanco Mesa

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Verde  
Sec. 5 T26N R8W

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7194' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 11 1981  
OIL CON. COM.  
DIST. 8

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Test results on the Mesa Verde zone indicate 100% formation water. We respectfully request permission to remove pump jack, pull rods and tubing. Place 5 sacks Class "B" cement on Production Packer at 4245' with wireline bailer. Run in hole with cast iron bridge plug, set at 3550', 40' above top of Mesa Verde formation. Place 5 sacks Class "B" cement on top of cast iron bridge plug with wireline bailer. Well will be a single completion as Ballard Pictured Cliffs (2026' - 2107'). Verbal approval granted at 3:52 P.M., MST, 5/4/81 by Mr. Richard Bell.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED Herma V. Wallis TITLE Exploration/Development Superintendent DATE May 4, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE MAY 8 1981

CONDITIONS OF APPROVAL, IF ANY:

*oh*

NMOCC

*Henry H. Luccasch, Jr.*  
FOR JAMES F. SIMS

DISTRICT OIL & GAS SUPERVISOR