

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
Supron Energy Corp. c/o John H. Hill, et al.

3. ADDRESS OF OPERATOR Kysar Building, Suite 020
300 W. Arrington, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1265' FNL & 940' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

SF - 078432

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

Hodges

9. WELL NO.

#21

10. FIELD OR WILDCAT NAME

Ballard Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 34 T26N R8W

12. COUNTY OR PARISH

San Juan


13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6686' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Total Depth, 6 1/4" hole, drilled to 2500'.
2. Ran 85 joints (2491.81') of new 2 7/8", 6.4# 10RD. NUE.
3. Set and cemented at 2491.81'.
4. Cemented with 400 sacks Class "B" cement, 50/50 Poz, 6% Gel, 1/2 cu.ft. Perlite. Tailed in with 150 sacks Class "B" cement.
5. Bump Omega Latch-down type plug with 1400# PSI, 7:00 P.M., 10/23/80, released pressure. Omega plug latched down. Circulated 10 barrels cement.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Herminio V. Waller Exploration and Development
TITLE Superintendent

DATE OCT 28 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMCCC