1. 1. 1. 1. 1. 1.

CONDITIONS OF APPROVAL, IF ANY:

## UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF - 078430  6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SURVEY	N/A
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME N/A
1 eil 700	8. FARM OR LEASE NAME Nickson
well gas well other	9. WELL NO.
2. NAME OF OPERATOR Supron Energy Corp. % John H. Hill, et al	11-E 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR Suite 020, Kysar Building	Pictured Cliffs/Dakota
300 W. Arrington, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 11 T26N R8W
AT SURFACE: 810' FNL & 1//0' FWL (NE NW)	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. AFI NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	6229\ GR
TEST WATER SHUT-OFF  FRACTURE TREAT	
SHOOT OR ACIDIZE	
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on form (1) 336.)
MULTIPLE COMPLETE	The last control of
CHANGE ZONES U U ABANDON*	081.3
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS Clearly statincluding estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertiner	irectionally drilled, give subsurface locations and
1. Logged well, ran Gamma Ray Correlation and C	CL logs
2. Perforated the Pictured Cliffs formation as	follows: 2216, 24, 26, 28,
30, 32, 34, 42, 44, 46. Total 10 holes with 3. Acidized with 1008 gallons 15% HCL acid and	
Ball Sealers, good ball action.	2% KCL water. Dropped 20- 7/6
4. Maximum Treating Pressure 1400 PSI, Minimum	
Average Treating Pressure 1200 PSI, ISDP 700 P.M., 4/22/81.	PSI. Job completed at 1:29
	·
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby pertify that the foregoing is true and correct	
SIGNED JURILLE SUPERINTENDENT DATE April 28, 1981	
(This space for Federal or State office use)	
•	DATE ASSEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:	Manci

**NMOCC** 

APR-3 0 1981