

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR
Supron Energy Corp. % John H. Hill, et al

3. ADDRESS OF OPERATOR Suite 020, Kysar Building
300 W. Arrington, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1010' FSL & 790' FWL (SW SW)

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐
☐

5. LEASE
SF - 078430

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A

7. UNIT AGREEMENT NAME
N/A

8. FARM OR LEASE NAME
Newsom "A"

9. WELL NO.
11

10. FIELD OR WILDCAT NAME
Ballard Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 3 T26N R8W

12. COUNTY OR PARISH 13. STATE


San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6925' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Logged well, ran Gamma Ray Correlation and CCL logs.
2. Perforated the Pictured Cliffs formation as follows: 2878, 80, 82, 84, 86, 88, 90, 92, 94 - 2904, 06, 20. Total 12 holes with Ceramic Strip.
3. Acidized with 1000 gallons 15% HCL acid and 2% KCL water.
4. Maximum Treating Pressure 2300 PSI, Minimum Treating Pressure 650 PSI, Average Treating Pressure 800 PSI, ISDP 450 PSI, Final Shut-In Pressure 450 PSI in 5 minutes. Job completed 12:00 A.M., 4/27/81.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ferman V. Waller

TITLE

Exploration/Development
Superintendent

DATE

April 28, 1981

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

APR 30 1981

FARMINGTON DISTRICT

BY

[Signature]

NMOCC

*See Instructions on Reverse Side