

SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☐ gas well ☒ other ☐

Supron Energy Corp. % John H. Hill, et al

3. ADDRESS OF OPERATOR Suite 020, Kysar Building
300 W. Arrington, Farmington, New Mexico 87401

AT SURFACE: 1790' FNL & 1080' FWL (SW NW)

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

X
/
/
/

5. LEASE
SF - 078384

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A

7. UNIT AGREEMENT NAME
N/A

8. FARM OR LEASE NAME
Newsom "B"

9. WELL NO.
13-E

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 9 T26N R8W

12. COUNTY OR PARISH San Juan	13. STATE New Mexico
----------------------------------	-------------------------

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6427' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Total Depth, 7 7/8" hole. Drilled to 7000'.
2. Ran 209 joints (7015.47') of new 4 1/2", 11.60#, J-55, R-3 ST&C casing.
3. Set and cemented at 6980.64'.
4. B.J. Hughes cemented in three stages. Hopper Specialty (B&W) stage tools set at 4582.70' and 2337.50'.
First Stage: 438 sx. 50/50 Poz, 2% Gel, 2% Calcium Chloride, .6% D-19
1/4 cu.ft. Perlite per sack. Stage tools failed. Set slips
on casing, 5:00 A.M., 2/21/81.

Moving in workover rig 2/27/81 to complete cement job by squeezing at appropriate intervals.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Herman C. Wallis TITLE Exploration/Development Superintendent DATE February 24, 1981

~~ACCEPTED FOR RECORD~~

(This space for Federal or State office use)

APPROVED BY FEB 26 1981
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

FARMINGTON DISTRICT
BY BW

NMOCC