

9-331
1973

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well

2. NAME OF OPERATOR
Energy Reserves Group, Inc.

3. ADDRESS OF OPERATOR
P.O. Box 3280 - Casper, Wyoming 82602

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1570' FSL & 1680' FWL (NE/SW)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Well History

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
NM-03153

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
O.H. Randel

9. WELL NO.
7-E

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 15-T26N-R11W

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
G.L. 6,311' K.B. 6,323'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drld 7-7/8" hole to 6,235' and ran logs; then, drilled to T.D. of 6,245'.
Ran 4-1/2" O.D., 10.5#, K-55, R-3, 8Rth, ST&C, new casing set @ 6,245' w/
stage collar @ 4,425'. Cemented 1st stage w/190 sx of 50-50 Pozmix w/1/4#
Flocele/sx; followed by 210 sx of Class "B" cement w/10% Salt & 1/4# Flocele/sx.
Cemented 2nd stage w/400 sx of 65-35 Pozmix w/6% Gel & 10# Gilsonite/sx; followed
by 655 sx of 50-50 Pozmix w/2% Gel & 12-1/2# Gilsonite/sx. Plug down @ 8:30 am,
2-2-81. Good circulation throughout both stages and circulated cement to surface
on 2nd stage.

2-3-81: M.O.R.T. & W.O.C.T.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R.C. Billigan TITLE Dr1g Supt- RMD

DATE

2-4-81

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NMOCO

*See Instructions on Reverse Side