UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE () () () () () () () () () (
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
	O.H. Randel
1. oil gas well other	9. WELL NO. 3453
2. NAME OF OPERATOR	6-E
Energy Reserves Group, Inc.	10. FIELD OR WILDCAT NAME Basin Dakota
3. ADDRESS OF OPERATOR P.O. Box 3280 - Casper, Wyoming 82602	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA 클립한글 등 등로 있다.
below.) AT SURFACE: 940' FSL & 790' FEL (SE/SE) AT TOP PROD. INTERVAL:	Sec. 15-T26N-R11W 12. COUNTY OR PARISH San Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15 FLEWTIONS (CHOW DE KDR AND WD)
	15. ELEVATIONS (SHOW DF, KDB, AND WD)G_L. 6,383' - K.B. 6,395'
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	D
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL SUBSEQUENT REPORT OF: U REPORT OF: SUBSEQUENT REPORT OF: OF: SUBSEQUENT REPORT OF: OF: OF: SUBSEQUENT REPORT OF: OF: OF: OF: OF: OF: OF: OF:	
SHOOT OR ACIDIZE TREPAIR WELL TO 199	81 (NOTE: Report results of multiple completion or zone change on Form 9–33(6)
	observe on Formit 220116
MULTIPLE COMPLETE CHANGE ZONES	SURVE
ABANDON*	W. M.
PULL OR ALTER CASING	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertined	te all partinost details and GWA Derrinent Names.
Drilled 7-7/8" hole to 6,347' & ran logs.	(**) (**) (**) (**) (**) (**) (**) (**)
Ran 164 jts 4-1/2" O.D., 10.5#, K-55, R-3 ner	w casing set @ 6.346'. w/DV tool
t for Compared 1st stage $W/250$ sx of $50-50$	() Pozmix w/2% Gel & 1/4# Flocele/sx;
c. 11 1 h 170 or of Clace "R" cement W/10%	Salt & 1/4# Flocele/sx. Cemented
2nd stage $w/500$ sx of 65-35 Pozmix $w/6\%$ Gel	& 10# Gilsonite/sx; followed by 330
sx of 50-50 Pozmix w/2% Gel & 12-1/2# Gilson	ite/sx. Plug down @ 4:00 PM 1-22-81.
	그 그 그 그는 그 생활하다 내용 사람들이 되었다.
	등본환경화 관한 상황, 회
	Set @ Ft.
Subsurface Safety Valve: Manu. and Type	
18. I hereby certify that the foregoing is true and correct	
SIGNED COLOR . Billengue TITLE Drlg Supt-R	MD DATE 1-26-81
(This space for Federal or State o	
ACCEPTED FOR RECORD APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY: FLB 0 4 1981	선명하실할 수 있을 표를 하는 것이 말했다.
NMOCE	
MAIOCO	

*See Instructions on Reverse Side