UNITED STATES DEPARTMENT OF THE INTERIOR - GEOLOGICAL SURVEY

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING

MULTIPLE COMPLETE CHANGE ZONES

REPAIR WELL

ABANDON*

(other)

Form 9-331 Dec. 1973	7	Approved. et Bureau No. 42-R1424	
UNITED STATES	5. LEASE		
DEPARTMENT OF THE INTERIOR	SF - 078430		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME N/A		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME N/A		
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME NICKSON 9. WELL NO.		
1. oil gas (X) other			
Well Well Other	#21		
2. NAME OF OPERATOR Supron Energy Corp. % John H. Hill, et al 3. ADDRESS OF OPERATOR Suite 020, Kysar Building	10. FIELD OR WILDCAT NAME Ballard Pictured Cliffs		
300 W. Arrington, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 11 T26N R8W		
AT SURFACE: 1850' FSL & 790' FWL (NW SW) AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH San Juan	13. STATE New Mexico	
AT TOTAL DEPTH:	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15 ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	, w		

(NOTE: Report results of multiple

change on Form 9-

AUG2 7 1981

OIL CON. COM.

DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Frac'd the Pictured Cliffs perforations (2230' 2260') with 13,314 gallons 70% Quality Foam, 2% KCL water and 38,861# 10/20 sand.
- Maximum Treating Pressure 4100 PSI, Minimum Treating Pressure 1600 PSI, Average Treating Pressure 2100 PSI, Final Shut-In Pressure 3600 PSI in 4 minutes. Job completed at 8:40 A.M., 8/18/81.

Subsurface Safety Valve: Manu. and Type				
18. I hereby certify that the foregoing is	true and correct Explorati Light ITLE Superinte	on/Development ndent	August 21, 19	981
	(This space for Federal or Stat	te office use)		
APPROVED BY	TITLE	DATE	and the second s	·
			3 2 5 1981	
	*See Instructions on Revo	erse Side ;	SAN	

NMOCC