

5 - USGS

1 - McHugh

1 - File

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other2. NAME OF OPERATOR  
Jerome P. McHugh3. ADDRESS OF OPERATOR  
P O Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 830' FNL - 2070' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒ perfs

5. LEASE

N00-C-14-20-4322

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Allotted

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chaco Plant

9. WELL NO.

18R

10. FIELD OR WILDCAT NAME

P.C. Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 13 T26N R12W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5990' GR

(NOTE) Report results of multiple completion or zone change on Form 9-330.7

MAY 10 1981  
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

3-18-81 Rigged up F.W.S. swabbing unit and Southwest Surveys. PBTD 1310'. Ran GR/CLL from TD to 500'. GR/CLL depths are set back to the open hole log. Swabbed well down to  $\pm$  1000'. Perf. 1214-1220', 6', 6 holes, 1 SPF w/ 2-1/8" bi-wire glass jets. Swabbed well dry in two runs. Gas ahead of swab during swabbing, no water entry indicated. Perf. 1172-1176, 4', 4 holes, 1 SPF w/ 2-1/8" bi-wire glass jets. Swabbed well dry; small amount of gas ahead of swab; no water entry indicated.

NOTE: These perfs in addition to the ones reported on the Sundry Notice of 4-29-81.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Thomas A. Dugan

TITLE

Agent

DATE

5-11-81

(This space for Federal or State office use)

RECEIVED FOR RECORD

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

MAY 15 1981

NMOCC

FARMINGTON DISTRICT

BY

E. A. H.