

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR  
Jerome P. McHugh

3. ADDRESS OF OPERATOR  
P O Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 830' FNL - 2070' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

**RECEIVED**

NOV 24 1982

U.S. GEOLOGICAL SURVEY  
FARMINGTON, NM

Amending Sundry Notice Dated 11-18-82)

5. LEASE  
N00-C-14-20-4322

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Navajo Allotted

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Chaco Plant

9. WELL NO.  
18R

10. FIELD OR WILDCAT NAME  
P.C. Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 13 T26N R12W

12. COUNTY OR PARISH  
San Juan

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5990' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plugged and abandoned this well in the following manner:

1. Filled 2-7/8" O.D., 6.4#, 10 Rd, CW-55, NEUE tubing for casing with 40 sacks cement.
2. Installed permanent dry hole monument.
3. Filled all pits.
4. Cleaned well location of all equipment, pipe, junk, and trash.
5. Restored surface per surface management agency's stipulations.
6. Cut off tie-downs.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

Set @ \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED Sherman E. Dugan  
Sherman E. Dugan

TITLE Agent

DATE 11-23-82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

**APPROVED  
AS AMENDED**

DEC 18 1984

M. MILLENBACH  
AREA MANAGER

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

See Instructions on Reverse Side