

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR
Southland Royalty Company

3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 840' FSL & 1800' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐


SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

Casing Report

5. LEASE
NM-28759
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal
9. WELL NO.
12-14
10. FIELD OR WILDCAT NAME
Basin Dakota/Gallegos Gallup
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 12, T26N, R11W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6463 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-27-81 Ran 158 joints (6654') of 5-1/2", 15.5#, K-55 casing set at 6668'. DV tools set at 4653' and 2258'. Cemented 1st stage with 175 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# flocele per sack. Tailed in with 50 sacks of Class "B" with 2% CaCl₂. Plug down at 5:30 P.M. 4-27-81. Cemented 2nd stage with 285 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# flocele per sack. Tailed in with 50 sacks of Class "B" with 2% CaCl₂. Plug down at 9:30 P.M. 4-27-81. Cemented 3rd stage with 270 sacks of Class "B" 50/50 Poz with 6% gel and 1/4# flocele per sack. Tailed in with 50 sacks of Class "B" with 2% CaCl₂. Plug down at 12:15 A.M. 4-28-81. Top of Cement at 500'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ester Guevara TITLE Drilling Clerk DATE April 28, 1981

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD

MAY 01 1981

*See Instructions on Reverse Side

NMOCG

FARMINGTON DISTRICT
BY [Signature]