

N. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-3148-7

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)


1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Hixon Development Company	8. Farm or Lease Name Chaco Wash Comm.
3. Address of Operator P.O. Box 2810, Farmington, New Mexico 87401	9. Well No. 1J
4. Location of Well UNIT LETTER <u>I</u> , <u>1850</u> FEET FROM THE <u>south</u> LINE AND <u>790'</u> FEET FROM THE <u>east</u> LINE, SECTION <u>32</u> TOWNSHIP <u>26 North</u> RANGE <u>12 West</u> NMPM.	10. Field and Pool, or Wildcat WAW-Fruitland-PC
15. Elevation (Show whether DF, RT, GR, etc.) 6092' GLE	12. County San Juan

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1/4/82 - Rig up James Drilling Company Rig No. 1. Spud well at 6:45 pm. Drill 9-7/8" hole to 79'. Run 2 joints (69.08') 7" 20# 8rd K-55 casing. Set at 70.58' GLE. Rig up Woodco Cementing and pump 35 sacks Class B cement with 2% CaCl. Circulate cement to surface. Displace with 2.2 BW. WOC 12 hours. Pressure test to 600 psi for 30 minutes on 1-5-82. Prepare to drill out from under surface.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Frank T Chavez TITLE Petroleum Engineer DATE January 6, 1982

APPROVED BY Original Signed by FRANK T CHAVEZ SUPERVISOR DISTRICT 3 DATE JAN 6 1982

CONDITIONS OF APPROVAL, IF ANY: