

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-3148-7	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator Hixon Development Company		8. Farm or Lease Name Chaco Wash Com.	
3. Address of Operator P.O. Box 2810, Farmington, New Mexico 87401		9. Well No. # 2	
4. Location of Well UNIT LETTER I, 1850 FEET FROM THE south LINE AND 790 FEET FROM THE east LINE, SECTION 32 TOWNSHIP 26 North RANGE 12 West NMPM.		10. Field and Pool, or Wildcat WAW-Fruitland-PC	
15. Elevation (Show whether DF, RT, GR, etc.) 6092' GLE		12. County San Juan	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1/6/82 Reach 1200' total depth at 11:50 am 1/6/82. Rig up Birdwell and run Induction Electric, Density-Neutron logs. Log tops as follows: Kirtland shale 151', Fruitland coal 1076', Pictured Cliffs sand 1060'. Set 2-7/8" 6.5# EUE 8rd casing at 1197'. Rig up Dowell and cement casing with 100 sacks 50-50 Litepoz 6 containing 2% CaCl, 2% gel and 1/4#/sack cellophane flakes, followed by 50 sacks Class B with 2% CaCl and 1/4#/sack cellophane flakes. Cement circulated to surface with full returns through-out job. Shut in well. WOC.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Frank T. Chavez TITLE Petroleum Engineer

DATE 1/11/82

Original Signed by FRANK T. CHAVEZ

SUPERVISOR 1/11/82

JAN 11 1982

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: