STATE OF NEW MEXICO ENERGY AND MITTERALS DEPARTMENT

· · · · · · · · · · · · · · · · · · ·		
	<u> </u>	
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		1

OIL CONSERVATION DIVISION

ee, er terite stativa	P. O. BOX 2088	Form C-103	
DISTRIBUTION SANTA FE	SANTA FE, NEW MEXICO 87501	Revised 10-1-78	
FILE	JANTA FE, NEW MEXICO 67501	Sa. Indicate Type of Lease	
U.3.G.S.	1	State X Fee	
LAND OFFICE		5. State Oil 6 Gas Lease No.	
OPERATOR]		
		E-3148-7	
SUNDR	RY NOTICES AND REPORTS ON WELLS OPPOSALS TO DRILL OR TO DEEPEN OF PLUG BACK TO A DIFFERENT RESERVOIR. 104 FOR PERMIT - (FORM C-1011 FOR SUCH PROPOSALS.)		
1. OIL CAS X WELL X	OTHER-	7. Unit Agreement Name	
2. Name of Operator		8. Farm or Lease Name	
Hixon Development Company		Chaco Wash Com.	
3. Address of Operator		9. Well No.	
P.O. Box 2810, Farmington, New Mexico 87401		1J	
4. Location of Well	Talmington, 100	10. Field and Pool, or Wildcar	
	1900 couth 790	WAW-Fruitland-PC	
UNIT LETTER	1800 FEET FROM THE SOUTH LINE AND 790 FEET FR	THITTINI ""	
	1011		
THE east LINE, SECTI	OH 32 TOWNSHIP 26N RANGE 12W NM	.w. (///////////////////////////////////	
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County	
	6092' GLE	San Juan	
16.	Appropriate Box To Indicate Nature of Notice, Report or	Other Data	
		ENT REPORT OF:	
NOTICE OF I	NTENTION TO: SUBSEQUE	IN THE SKI OF I	
<u> </u>		ALTERING CASING	
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	=	
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT	
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB X	П	
	OTHER		
OTHER			
	20 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	line estimated date of starting any proposed	
17. Describe Proposed or Completed Operat) SEE RULE 1103.	perations (Clearly state all pertinent details, and give pertinent dates, includ	ing commerce date of statement only proposed	
Reached 1326'	total depth at 4:30 am on 1/23/82. Tops as foll	lows: Kirtland	
shale 151', Fr	uitland coal 1036', Pictured Cliffs sand 1060'.	Set 2-7/8" 6.5#	
	21'. Rig up Dowell and cement casing as follows		
	s B 50:50 Literoz cement containing 2% CaCl, 2%		

100 sacks Class B 50:50 Litepoz ce cellophane flakes. Tail in with 50 sacks Class B cement containing 2% CaCl. Circulate cement to surface. WOC.

	7 - 4 - 4 - 1	OR CON COM
18. I hereby certify that the information above is true and comple	te to the best of my knowledge and belief. Outs Petroleum Engineer	DATE 1/28/82
Original Signed by FRANK T. CHAVEZ	SUPERVISOR DISTRICT # 3	FEB 1 1982